



All dimensions are in mm; tolerances acc. to ISO 2768 m-H

**Interface**

According to MIL-STD-348

**Documents**

Assembly instruction 19 E8

**Material and plating**

**Connector parts**

Center contact  
Outer contact  
Dielectric

**Material**

CuBe  
CuBe  
PTFE

**Plating**

AuroDur®, gold plated  
AuroDur®, gold plated

**Electrical data**

Impedance	50 Ω
Frequency	DC to 26.5 GHz
Return loss	≥ 35 dB @ DC to 2 GHz ≥ 30 dB @ 2 GHz to 12 GHz ≥ 20 dB @ 12 GHz to 26 GHz
Insertion loss	≤ 0.1 x √f [GHz] dB
Insulation resistance	≥ 5 GΩ
Center contact resistance	≤ 6 mΩ
Outer contact resistance	≤ 2 mΩ
Test voltage (at sea level)	500 V rms
Working voltage (at sea level)	335 V rms
Contact Current	≤ 1.2A DC

- Limitations are possible due to the used cable type -

**Mechanical data**

Mating cycles	
if mating part is Smooth bore, Catcher's Mitt	≥ 1000
if mating part is Limited detent	≥ 500
if mating part is Full detent	≥ 100
Center contact captivation	≥ 7 N
Engagement force	
- Smooth bore, Catcher's Mitt	≤ 9 N
- Limited detent	≤ 45 N
- Full detent	≤ 68 N
Disengagement force	
- Smooth bore, Catcher's Mitt	≥ 2.2 N
- Limited detent	≥ 9 N
- Full detent	≥ 22 N

**Environmental data**

Temperature range	-65 °C to +155 °C
Rapid change of temperature	IEC 60068-2-14 (-65 °C to 155 °C, 1h dwell, 50 cycles)
Vibration	MIL-STD-202, Method 204, Condition B
Shock	MIL-STD-202, Method 213, Condition A
Damp heat	IEC 60068-2-78 (40°C, 93% RH, 56d)
High temperature endurance	IEC 61169-1, Sub-clause 9.6 (+155 °C, 1000 hours)
RoHS	compliant

**Tooling**

N/A

**Suitable cables**

UT 85, RG 405 /U, RTK-FS 085

**Weight**

Weight 0.5 g/pc

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
S. Mühlbacher	06.02.17	S. Mühlbacher	07.02.17	a00	17-0005	A_Wallner	07.02.17

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.de">www.rosenberger.de</a>				Tel. : +49 8684 18-0 Email : <a href="mailto:info@rosenberger.de">info@rosenberger.de</a>		Page 2 / 2	
--	--	--	--	--	--	---------------	--