

## Datasheet

# RS PRO 12V dc Power Supply

Stock No: 1440971



# Features and Benefits:

- 1800mm Cable
- Level VI efficiency
- 3 Pin IEC plug
- (C14) Input connector
- Universal input 90-264 V-AC 47-63 Hz
- 0-40°C Operating temperature
- RoHS-REACH Compliant
- Very low power consumption <0.10W ERP II Regulation compliant
- Approved to UL, cUL, FCC, CB, SAA, REACH & RoHS

## Specifications

<b>Attribute</b>	<b>Value</b>
Input Voltage Range	100 → 240 V ac
Output Voltage Rating	12V dc
Output Current Range	0 → 2.5A
Rated Output Power	30W
Input Connector	IEC C14
Output Connection Type	2.1 x 5.5 mm Connector
Number of Outputs	1
Plug Type	3-Pin IEC
Minimum Temperature	0°C
Maximum Temperature	+40°C
Overall Length	99mm
Efficiency	87%
Standards Met	AS/NZS 60950.1, BS EN 60950-1, CB, CE, CSA C22.2 No.60950-1-07, cUL, EN 60950-1, FCC, J60950-1, SAA, TUV, UL, UL 60950-1
Cable Length	1800mm
Operating Temperature Range	0 → +40 °C
Overall Dimensions	99 x 52 x 36mm
Energy Efficiency Level	VI
Series	HK-AB
Overall Width	52mm
Overall Depth	36mm
Holdup Time	10 (Minimum)ms