

## Eaton XT IEC mini contactor

DILM9-10(24V60HZ)

### Dimensions:

- **Height:** 2 IN
- **Length:** 2 IN
- **Width:** 3 IN

**Weight:** .3 LB

**Notes:** Screw terminals (6-65A), 5 mm (80-150A), no lugs (185-2000A)

### Warranties:

- 1 year

### Specifications:

- **Amperage Rating:** 9A
- **Coil:** 24V 60 Hz
- **Coil Voltage:** 24 Vac, 60 Hz
- **Contact Configuration:** 1NO
- **Frame Size:** 45 mm
- **Frequency Rating:** 60 Hz
- **Max Hp Rating:** 0.5, 1.5/ 3, 3, 5, 7.5 (1/3PH @120,240/208,240,480,575 V)
- **Number Of Poles:** Three-pole
- **Operation:** Non-reversing
- **Series:** XT IEC series
- **Terminals:** Screw terminals
- **Type:** Full voltage non-reversing miniature contactor
- **Wattage:** 4 kW

### Supporting documents:

- [Product Data Sheet - DILM9-10\(24V60HZ\)](#)
- [Eaton Specification Sheet - DILM9-10\(24V60HZ\)](#)

### Certifications:

- EN 60947
- UL Listed
- IEC 60947



- CSA Certified

**Product compliance:**

- RoHS Compliant
- CE Marked

---

© 2016 Eaton. All rights reserved.