

Eaton Type MTE industrial control transformer

C0075E5EFBQ

UPC:786680421754

Dimensions:

- Height: X
- Length: X
- Width: X

Notes: Epoxy encapsulated, Laminations of high quality silicon steel to minimize core losses and optimize performance, 50/60Hz operation, 130°C insulation system standard, Molded-in terminals for maximum durability

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Coil Material:** Copper windings
- **Design:** MTE
- **Modification 1:** Factory-mounted 2-pole primary fuse block for rejection type fuses
- **Modification 2:** Secondary fuse clips for 1/4 X 1-1/4 inch fuses
- **Primary Voltage:** 200/220/440V, 208/230/460V, 240/480V
- **Secondary Voltage:** 23/110V, 24/115V, 25/120V
- **Tap Size:** None
- **Temperature Rating:** 55°C
- **Type:** Industrial Control Transformer
- **Volt Ampere Rating:** 75 VA

Supporting documents:

- [Industrial control transformers brochure](#)



- dry-type distribution transformer-flex center line card
- Transformer distribution catalog, volume 2, tab 2
- Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions
- Control Transformer Final Assembly - C0075E5EFBQ
- Transformer consulting application guide
- Eaton Specification Sheet - C0075E5EFBQ

Certifications:

- cUL Certified
- UL Listed
- CSA Certified

Product compliance:

- RoHS Compliant