



## DS7 Soft Start Controller

**DS7-340SX200N0-N**

**UPC:**786685883830

### Dimensions:

- **Height:** 7.01 IN
- **Length:** 8.46 IN
- **Width:** 4.25 IN

**Weight:**8.16 LB

**Notes:**No internal radio interference suppression filters

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Bypass:** Internal
- **Circuit Breaker Type:** HLD3500
- **Fuse Size:** 500A class RK5 max
- **Control Voltage:** 24 Vac/Vdc
- **Environmental Rating:** IP20
- **Frame Size:** Frames 3 and 4
- **Horsepower:** 150 hp
- **Phase:** Three-phase mains supply voltage
- **Rated Operational Current:** 200A
- **Series:** Generation 7
- **Voltage Rating:** 480V

### Supporting documents:

- [Eatons Volume 6-Solid-State Motor Control](#)
- [Product Datasheet - DS7-340SX200N0-N](#)
- [DS7 series soft start controllers, Frame 2 \(16-32A\)](#)
- [DS7 Series soft start controller](#)
- [Eaton Specification Sheet - DS7-340SX200N0-N](#)

**Certifications:**

- IEC 60947-4-2
- UL Listed
- EN 60947-4-2
- CSA Certified

**Product compliance:**

- CE Marked
- C-Tick Compliant

---

© 2016 Eaton. All rights reserved.