Eaton heavy duty single-throw non-fused safety switch

DH361UDK-LS

UPC:782113847863

Dimensions:

Height: 14.14 INLength: 10.22 INWidth: 8.76 IN

Weight:17 LB

Notes:Suitable for service entrance use with a neutral or ground lug kit installed. Can be field modified to meetNEMA 3R rainproof requirements when a factory provided drain hole is opened.

Warranties:

• Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

Special Features: Long enclosure

• Type: Single-throw

• Amperage Rating: 30A

• Enclosure: NEMA 12

• Enclosure Material: Painted galvanized steel

• Fuse Configuration: Non-fusible

• Number Of Poles: Three-pole

• Number Of Wires: Three-wire

• Product Category: Heavy Duty, Non-Fusible

Voltage Rating: 600∨

 Max Hp Rating: 7.5 at 480 Vac TD 1 Ph, 10 at 600 Vac TD 1 Ph, 10 at 240 Vac TD 3 Ph, 20 at 480 Vac TD 3 Ph, 30 at 600 Vac TD 3 Ph, 5 at 250 Vdc

Supporting documents:

• Eatons Volume 2-Commercial Distribution



• Eaton Specification Sheet - DH361UDK-LS

Certifications:

• UL Listed

Product compliance: No Data

© 2016 Eaton. All rights reserved.