

Contactor Accessory - Auxiliary Contact

XTCEXFAC13

Dimensions:

- **Height:** 7.1 IN
- **Length:** 2.5 IN
- **Width:** 4.5 IN

Weight:.01 LB

Notes:Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.

Warranties: No Data

Specifications:

- **Type:** Contactor Accessory - Auxiliary Contact
- **Used With:** XTRE control relays
- **Conventional Thermal Current:** 16A
- **Contact Configuration:** 1NO-3NC
- **Number Of Poles:** Four-pole
- **Quantity:** 5
- **Rated Operational Current:** 6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V
- **Terminals:** Screw terminals

Supporting documents:

- [Eaton's Volume 5-Motor Control and Protection](#)
- [Eaton Specification Sheet - XTCEXFAC13](#)
- [Global Data Sheet - XTCEXFAC13](#)

Certifications:

- IEC 60947
- EN 60947
- UL Listed
- CSA Certified



Product compliance:

- CE Marked
- ATEX Compliant
- CCC Marked

© 2016 Eaton. All rights reserved.