

## Eaton Type MTE industrial control transformer

C0100E2PXXFB

UPC:786680031496

### Dimensions:

- Height: X
- Length: X
- Width: X

**Notes:**Epoxy encapsulated, Laminations of high quality silicon steel to minimize core losses and optimize performance, 50/60Hz operation, 130°C insulation system standard, Molded-in terminals for maximum durability

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Coil Material:** Copper windings
- **Design:** MTE
- **Modification 1:** No secondary fuse clips
- **Modification 2:** Factory-mounted 2-pole primary fuse block for rejection type fuses
- **Primary Voltage:** 208/277/380V
- **Secondary Voltage:** 115/95V
- **Tap Size:** None
- **Temperature Rating:** 55°C
- **Type:** Industrial Control Transformer
- **Volt Ampere Rating:** 100 VA

### Supporting documents:

- [dry-type distribution transformer-flex center line card](#)
- [Industrial control transformers brochure](#)
- [Transformer distribution catalog, volume 2, tab](#)



2

- Eaton's Volume 7-Logic Control, Operator Interface and Connectivity Solutions
- Transformer consulting application guide
- Eaton Specification Sheet - C0100E2PXXFB

**Certifications:**

- UL Listed
- cUL Certified
- CSA Certified

**Product compliance:**

- RoHS Compliant