

Eaton XT IEC contactor

DILM40(24V60HZ)

Dimensions:

- **Height:** 4.5 IN
- **Length:** 2.2 IN
- **Width:** 5.2 IN

Weight:1.98 LB

Notes:Screw terminals (6-65A); 5 mm (80-150A);
no lugs (185-2000A)

Warranties:

- 1 year

Specifications:

- **Amperage Rating:** 40A
- **Coil:** 24V 60 Hz
- **Coil Voltage:** 24 Vac, 60 Hz
- **Contact Configuration:** 0NO-0NC
- **Frame Size:** 55 mm
- **Frequency Rating:** 60 Hz
- **Max Hp Rating:** 3, 7.5/ 10, 15, 30, 40 (1/3PH
@ 120,240/208,240,480,600 V)
- **Number Of Poles:** Three-pole
- **Operation:** Non-reversing
- **Series:** XT IEC series
- **Terminals:** Screw terminals
- **Type:** Full voltage non-reversing contactor
- **Wattage:** 18.5 kW

Supporting documents:

- [Eaton Specification Sheet - DILM40\(24V60HZ\)](#)
- [Global Data Sheet - DILM40\(24V60HZ\)](#)

Certifications:

- CSA Certified
- EN 60947
- IEC 60947
- UL Listed



Product compliance:

- CE Marked
- RoHS Compliant

© 2016 Eaton. All rights reserved.