

## Eaton 35SS commercial meter stack

**35SS220RAB**

**UPC:**782114055045

### **Dimensions:**

- **Height:** 16 IN
- **Length:** 45 IN
- **Width:** 20 IN

**Weight:**130 LB

**Notes:**Main tenant feeders can exit top, bottom, or back, If being used in outdoor application and exiting the top, mount Myer type hubs on rainproof cap. 120/240V, single-phase, three-wire systems and 208Y/120V network metering

### **Warranties:**

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### **Specifications:**

- **Voltage Rating:** 120/240V
- **Amperage Rating:** 200A
- **Bus Material:** Aluminum
- **Bus Rating:** 1200 A
- **Bypass:** Test
- **Enclosure:** Indoor/outdoor
- **Number Of Jaws:** Five-jaw
- **Number Of Sockets:** 2
- **Phase Balance:** A-B
- **Secondary Circuit Breaker:** EHD2\_, CCV2\_X, CCVH2\_X, CVS2\_X, CV2\_X,CVH2\_X
- **Security:** Ring
- **Socket Amperage:** 225A

**Supporting documents:** No Data

**Certifications:**

- UL Listed

**Product compliance:**

- EUSERC Approved

---

© 2016 Eaton. All rights reserved.