PARKER 3-WAY NORMALLY CLOSED, 1/4" NPT GENERAL PURPOSE SOLENOID VALVES

☑ Email ♣ Print



Click for Larger View

Parker 3-Way Normally Closed, 1/4" NPT Solenoid Valves provide operating pressures up to 250 psi and flow factors up to 0.67 CV's. They come in stainless with multiple mounting positions and coil options for all general purpose flow control applications.

PART NUMBER:

71315SN2GVJ1N0H111C2

VOLTAGE (V):

24 VDC

SEAL MATERIAL:

FKM

ORIFICE MAIN (INCH):

1/16

FLOW FACTOR MAIN (CV):

0.11

POWER (WATTS):

10 Watt (DC)

COIL TYPE:

1/2" NPT Conduit, 18" Leads, Class F, NEMA 7, 9

MAXIMUM PRESSURE DIFFERENTIAL (PSI):

200 psi (DC)

MECHANICAL OPTION:

Exhaust Adapter Nut



QUA	NTITY:		
_	1	+	Part(s)

Reset Attributes

GET A QUOTE

PRODUCT OVERVIEW +
TECH SPECIFICATIONS -

WHERE TO BUY

Print Tech Specifications

PERFORMANCE CHARACTERISTICS

PRODUCT SERIES

7000 Series

VALVE TYPE

3-Way

FUNCTION

Normally Closed

PORT SIZE

1/4 inch

INPUT VOLTAGE

24 VDC

BODY MATERIAL

Stainless

SEAL MATERIAL

 FKM

MAIN ORIFICE SIZE



MAIN FLOW COEFFICIENT 0.11 Cv **POWER CONSUMPTION** 10 Watt (DC) W **COIL TYPE** 1/2" NPT Conduit, 18" Leads, Class F, NEMA 7, 9 **MAXIMUM PRESSURE DIFFERENTIAL** 200 psi (DC) psi **ADDITIONAL OPTIONS** Exhaust Adapter Nut **NUMBER OF PORTS** 3 **ACTUATION TYPE Direct Acting MEDIA** General Purpose for Air, Liquids and Gases **PORT TYPE** NPT **EXHAUST ORIFICE SIZE** 1/16 inch **EXHAUST FLOW COEFFICIENT** 0.095 Cv **ORIFICE 2 SIZE** n/a **FLOW COEFFICIENT 2** n/a MINIMUM PRESSURE DIFFERENTIAL

0 psi

MINIMUM FLUID TEMPERATURE

0 °F

MAXIMUM FLUID TEMPERATURE

185 °F

COIL SPECIFICATIONS MET

 \odot

Print Tech Specifications

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE. This document and other information from Parker-Hannifin Corporation, its subsidiaries and authorized distributors provide product or system options for further investigation by users having technical expertise. The user, through its own analysis and testing, is solely responsible for making the final selection of the system and components and assuring that all performance, endurance, maintenance, safety and warning requirements of the application are met. The user must analyze all aspects of the application, follow applicable industry standards, and follow the information concerning the product in the current product catalog and in any other materials provided from Parker or its subsidiaries or authorized distributors. To the extent that Parker or its subsidiaries or authorized distributors provide component or system options based upon data or specifications provided by the user, the user is responsible for determining that such data and specifications are suitable and sufficient for all applications and reasonably foreseeable uses of the components or systems. Click here to view all product safety information.

CAD +

PRODUCT SUPPORT

RECOMMENDED



Parker 2-Way Normally Closed, 1-1/4" NPT General Purpose Solenoid Valves



Parker 2-Way Sinclair Collins K Series, Normally Open, 1" **Process Control Valves**



Parker 2-Way Sinclair Collins K Series, Normally Closed, 1/2" Process Control Valves



Parker 2-Way S Collins K Seri Normally Open Process Control

FOLLOW US

Follow Parker Hannifin on social media:















CONTACT US

Fluid Control Division 95 Edgewood Avenue New Britain, CT 06051 **United States**



Phone Fax 860-827-2300 860-827-2384

Parker Hannifin +

Products About Parker

Investors Community

Careers

Global Operations +

Divisions Sales Companies

Worldwide Locations Distribution Network

ParkerStore™ Network

Company Information +

Newsroom Event Calendar

Working with Parker Product Brands

History

Global Support Center

Support CAD

Where to Buy Contact Parker

Manage Online Orders

ENGINEERING YOUR SUCCESS.

SITE MAP | SAFETY | PRIVACY POLICIES
TERMS AND CONDITIONS

© PARKER HANNIFIN CORP 2021

