

## 26W75

20 Amp, 250 Volt 3-Phase, NEMA L15-20P, 3P, 4W, Locking Plug, Industrial Grade, Grounding, Wetguard - YELLOW

Leviton's Wetguard line of industrial watertight wiring devices are the most versatile, well-engineered watertight devices on the market. They meet IP67 and NEMA ratings for water ingress protection, and offer many significant advantages over competitive brands.



UPC Code : 078477968093

Country Of Origin : United States

RoHS Compliant : Yes



Available Colors :



### Technical Information

#### Electrical Specifications

**Amperage** : 20 A

**Current Limiting** : Full Rated Current

**Dielectric Voltage** : Withstands 2000V per UL498

**Grounding** : Grounding

**Phase** : 3-Phase

**Pole** : 3

**Temperature Rise** : Max 30C after 250 cycles OL at 200 percent rated current

**Voltage** : 250 VAC

**Wire** : 4

#### Environmental Specifications

**Environment** : Wet

**Flammability** : Rated V-2 per UL 94

**IP Rating** : IP66, IP67, IP69K

**Operating Temperature** : -40°C to 60°C

#### Material Specifications

**Assembly Screws** : Stainless Steel 300

**Blades/Contacts** : Nickel-Plated Brass

**Body Interior** : Nylon

**Body Material** : EPTR Rubber

**Bushing** : Santoprene TPV

**Compression Nut, Strain Relief** : Nylon

**Terminal Screws** : Electroless Nickel-coated Brass

**Wire Module** : Nylon

#### Mechanical Specifications

**Cord Grip Range (in)** : .375-.875

**Product ID** : Ratings and NEMA I.D. permanently marked on device

**Terminal Accom.** : #16 to #10

**Terminal ID** : Brass-Hot, Green-Ground, Silver-Neutral

#### Product Features

**Assembly Screws** : Stainless Steel 300

**Blades/Contacts** : Nickel-Plated Brass

**Body Material** : EPTR Rubber

**Brand** : Wetguard

**Color** : Yellow

**Device Type** : Locking Plug

**NEMA** : L15-20P

**Standards and Certifications** : UL/CSA

#### Standards and Certifications

**ANSI** : C-73


**CSA C22.2 No. 42** : File LR-406

**NEMA** : WD-6

**NOM** : 057

**UL** : 498

**Warranty** : Limited Lifetime Warranty Warranty



## SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):

+1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

