

# 2716

30 Amp, 125/250 Volt, NEMA L14-30R, 3P, 4W, Flanged Outlet Locking Receptacle, Industrial Grade, Grounding - WHITE



UPC Code : 078477806456

Country Of Origin : United States

RoHS Compliant : Yes



Leviton's industry leading locking devices, such as our Black & White line of industrial grade plugs and connectors and our V-0-Max line of industrial grade flush receptacles, offer superior performance, long lasting reliability and other features that are backed by a lifetime warranty.

## Technical Information

### AC Horsepower Ratings

**At Rated Voltage** : 2 HP L-L / 2 HP L-N

### Electrical Specifications

**Amperage** : 30 A

**Current Limiting** : Full Rated Current

**Dielectric Voltage** : Withstands 2000V per UL498

**Grounding** : Grounding

**Pole** : 3

**Temperature Rise** : Max 30C after 250 cycles OL at 200 percent rated current

**Voltage** : 125/250 VAC

**Wire** : 4

### Environmental Specifications

**Environment** : Dry

**Flammability** : Rated V-2 per UL 94

**Operating Temperature** : -40°C to 60°C

### Material Specifications

**Body Material** : Nylon

**Color** : White

**Face Material** : Nylon

**Grounding Screw** : Brass 8-32

**Line Contacts** : Solid Brass

**Strap Material** : Thermoplastic Nylon

**Terminal Screws** : Brass 10-32

### Mechanical Specifications

**Product ID** : Ratings and NEMA I.D. permanently marked on device

**Screw Terminal Torque** : 10-14 in-lbs

**Terminal Accom.** : 18-10 AWG

**Terminal ID** : Brass-Hot, Green-Ground, Silver-Neutral

**Termination** : Back

**Torque Range** : 10-14 in-lbs

### Product Features

**Brand** : Black and White

**Color** : White

**Device Type** : Locking Flanged Outlet

**NEMA** : L14-30R

### Standards and Certifications

**ANSI** : C-73

**CSA C22.2 No. 42** : File LR-406

**NEMA** : WD-6


**NOM** : 057

**UL Fed Spec WC-596** : File E13393

**UL498** : File E13393

**Warranty** : Limited Lifetime Warranty Warranty

## Wiring Diagram



## SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):

+1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

