SIEMENS

Data sheet US2:52BT6D5AB



Figure similar

30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit PTT / Illuminated Pushbutton Full Voltage, 24V AC/DC LED Lamp Extended Button Plastic Lens, Blue 2 Position Momentary with 1 N.O. - 1 N.C. Heavy Duty Contacts, A600/P600 UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

Enclosure		
number of command points	1	
delivery state as a kit	No	
Actuator		
product extension optional light source	Yes	
material of the actuating element	plastic	
shape of the actuating element	Raised pushbutton	
number of contact modules	1	
type of unlocking device	without	
number of switching positions	2	
Front ring		
product component front ring	Yes	
design of the front ring	standard	
material of the front ring	metal	
color of the front ring	black	
Contact block/ lampholder		
number of lampholders	1	
Display		
number of LED modules	1	
General technical data		
product function positive opening	Yes	
product component		
 lamp transformer 	No	
light source	Yes	
insulation voltage rated value	600 V	
type of voltage		
of the operating voltage	AC/DC	
of the input voltage	AC/DC	
surge voltage resistance rated value	4 kV	
protection class IP	IP66	
• of the terminal	IP20	
thermal current	10 A	
Supply voltage		
type of voltage of the supply voltage of the light source	AC/DC	
supply voltage of the light source at AC at 60 Hz		
rated value	28 24 V	
supply voltage of the light source at DC		
rated value	28 24 V	

Auxiliary circuit		
number of NC contacts for auxiliary contacts	1	
number of NO contacts for auxiliary contacts	1	
operational current at AC-15		
at 110 V rated value	60 A	
 at 230 V rated value 	30 A	
 at 400 V rated value 	15 A	
 at 500 V rated value 	12 A	
Connections/ Terminals		
type of electrical connection	screw-type terminals	
tightening torque of the screws in the bracket	20 N·m	
tightening torque [lbf·in] with screw-type terminals	8 8 lbf·in	
Lamp		
color of the light source	blue	
Ambient conditions		
ambient temperature		
 during operation 	-35 +70 °C	
 during storage 	-40 +85 °C	
Installation/ mounting/ dimensions		
shape of the installation opening	round	
Certificates/ approvals		
Further information		

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52BT6D5AB

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52BT6D5AB

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/US2:52BT6D5AB Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52BT6D5AB&lang=en

last modified:	5/31/2021 🖸
----------------	-------------