



Busbar system, accessories Busbar center-to-center spacing 60 mm  
 Busbar support 3-pole for busbars 12x 5 (10)-30x 5 (10) Internal fixing with large clearances with large creepage distances according to UL 508

Model	
product brand name	SETRON
operating voltage / at AC / rated value	690 V
type of connectable conductor cross-sections / for copper conductor / stranded	12 mm x 5 mm - 30 mm x 10 mm
Mechanical Design	
busbar center-to-center spacing	60 mm
General Product Approval	



Test Certificates	Marine / Shipping	other
<a href="#">Special Test Certificate</a> <a href="#">Miscellaneous</a>	 	<a href="#">Confirmation</a> <a href="#">Miscellaneous</a>

**Further information**

- Information- and Downloadcenter (Catalogs, Brochures,...)  
<http://www.siemens.com/lowvoltage/catalogs>
- Industry Mall (Online ordering system)  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1923-3UA01>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)  
<https://support.industry.siemens.com/cs/ww/en/ps/8US1923-3UA01>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)  
[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8US1923-3UA01](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1923-3UA01)
- CAX-Online-Generator  
<http://www.siemens.com/cax>
- Tender specifications  
<http://www.siemens.com/specifications>



