

SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES ASSEMBLED LOAD CENTER. MAIN BREAKER WITH 8 1-INCH SPACES ALLOWING MAX 16 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (200A) 22KAIC. SPECIAL FEATURES: ALUMINUM BUS, FEED THRU LUGS, GREY TRIM NEMA TYPE 3R ENCLOSURE FOR OUTDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	16
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	200 A
voltage between phase and Ground (GND) rated value	120 V
voltage between phase and phase rated value	240 V
Model	
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM/ FEED THRU LUGS
Mechanical Design	
number of modular width units for installation width	8
size of the circuit-breaker	200A
General product approval	
certificate of suitability	UL

last modified:

7/9/2021 

