

## Eaton Type MTE industrial control transformer

**CE0100E4DCEFS**

**UPC:**786680035128

### **Dimensions:**

- **Height:** X
- **Length:** X
- **Width:** X

**Notes:**Epoxy encapsulated, Laminations of high quality silicon steel to minimize core losses and optimize performance, 50/60Hz operation, 130°C insulation system standard, Molded-in terminals, Non-short circuit-proof

### **Warranties:**

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### **Specifications:**

- **Coil Material:** Copper windings
- **Design:** MTE
- **Modification 1:** Factory-mounted finger-safe terminal shields
- **Primary Voltage:** 380/400/415V
- **Secondary Voltage:** 110/120V
- **Tap Size:** None
- **Temperature Rating:** 55°C
- **Type:** CE Marked Control Transformer
- **Volt Ampere Rating:** 100 VA

### **Supporting documents:**

- [dry-type distribution transformer-flex center line card](#)
- [Industrial control transformers brochure](#)
- [Transformer distribution catalog, volume 2, tab 2](#)

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [Transformer consulting application guide](#)
- [Eaton Specification Sheet - CE0100E4DCEFS](#)

**Certifications:**

- CSA Certified
- IEC 61558-2
- UL Listed
- cUL Certified

**Product compliance:**

- RoHS Compliant