UNIPAK, Low Voltage Fixed Capacitor Banks

10023PMURF

UPC:782116058525

Dimensions:

Height: 36 INLength: 11.978 INWidth: 19.3 IN

Weight: 104 LB

Notes:Multiply the 240V kVAR rating by 0.75 to calculate the kVAR value at 208V.

Warranties:

 Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

• Type: UNIPAK

Amperage Rating: 240AEnclosure: NEMA 1, 3R

 Enclosure Material: 14 ga. steel finished w/durable powder coat finish

• Frame Size: C2

- Fuse Type: Three slottedblade type fuses with 200,000 ampere interrupting capacity, Fuses mounted on stand-off bushings or fuse blocks, solderless connectors for easy hookup of incoming line conductors.
- Indicator: Red, neon blown-fuse indicating lights are protected by transparent weatherproof guard

• Phase: Three-phase

• Product Category: Low Voltage Fixed

Capacitor Banks

Protection: Three fuses, three lights

Rating: 100 kVARVoltage Rating: 240V

Supporting documents:

 Eatons Volume 3-Power Distribution and Control Assemblies

• Eaton Specification Sheet - 10023PMURF

Certifications:

- UL Listed
- CSA Certified

Product compliance: No Data

© 2016 Eaton. All rights reserved.