pe.eaton.com

# UNIPAK, Low Voltage Fixed Capacitor Banks

## 14023PMURF

UPC:786685139791

#### **Dimensions:**

- Height: 36 IN
- Length: 16.8 IN
- Width: 19.3 IN

## Weight:137 LB

**Notes:**Multiply the 240V kVAR rating by 0.75 to calculate the kVAR value at 208V.

#### Warranties:

• Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

# **Specifications:**

- Type: UNIPAK
- Amperage Rating: 336A
- Enclosure: NEMA 1, 3R
- Enclosure Material: 14 ga. steel finished w/durable powder coat finish
- Frame Size: D1
- Fuse Type: Three slottedblade type fuses with 200,000 ampere interrupting capacity, Fuses mounted on stand-off bushings or fuse blocks, solderless connectors for easy hookup of incoming line conductors.
- Indicator: Red, neon blown-fuse indicating lights are protected by transparent weatherproof guard
- Phase: Three-phase
- **Product Category:** Low Voltage Fixed Capacitor Banks
- Protection: Three fuses, three lights

- Rating: 140 kVAR
- Voltage Rating: 240∨

# Supporting documents:

- Eatons Volume 3-Power Distribution and Control Assemblies
- Eaton Specification Sheet 14023PMURF

# **Certifications:**

- CSA Certified
- UL Listed

Product compliance: No Data

© 2016 Eaton. All rights reserved.