

## Eaton Series C electronic molded case circuit breaker

**KD3125T57WZG**

**UPC:**782113943909

### **Dimensions:**

- **Height:** 5 IN
- **Length:** 8.5 IN
- **Width:** 5 IN

**Weight:**3 LB

### **Warranties:**

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### **Specifications:**

- **Type:** OPTIM 550
- **Amperage Rating:** 125A
- **Interrupt Rating:** 65 kAIC at 240 Vac, 35 kAIC at 480 Vac
- **Number Of Poles:** Three-pole
- **Voltage Rating:** 600 Vac, 250 Vdc
- **Trip Type:** Electronic LSIA
- **Circuit Breaker Type:** KD
- **Circuit Breaker Frame Type:** Complete breaker
- **Frame Size:** K-frame
- **Series:** Series C
- **Terminals:** Without terminals
- **Communication:** Zone selective interlock
- **Frequency Rating:** 50/60 Hz

### **Supporting documents:**

- [Application of Multi-Wire Terminals for Molded Case Circuit Breakers](#)
- [Application of Tap Rules to Molded Case Breaker Terminals](#)

- [UL listed 100%-rated molded case circuit breakers](#)
- [Plug-in adapters for molded case circuit breakers product aid](#)
- [Multi-wire lugs product aid](#)
- [Current limiting Series C molded case circuit breakers product aid](#)
- [Circuit breaker motor operators product aid](#)
- [StrandAble terminals product aid](#)
- [Power metering and monitoring with Modbus RTU product aid](#)
- [Motor protection circuit breakers product aid](#)
- [Eatons Volume 4-Circuit Protection](#)
- [Molded case circuit breakers](#)
- [Breaker service centers](#)
- [MOEM MCCB product selection guide](#)
- [Series C G-Frame molded case circuit breakers time current curves](#)
- [Series C F-Frame molded case circuit breakers](#)
- [Eaton Specification Sheet - KD3125T57WZG](#)
- [Series C J-Frame molded case circuit breakers time current curves](#)

**Certifications:**

- [UL Listed](#)

**Product compliance:** No Data