

## Eaton XT IEC mini contactor

### DILM7-01(24V60HZ)

#### Dimensions:

- **Height:** 2.7 IN
- **Length:** 1.8 IN
- **Width:** 3 IN

**Weight:** .48 LB

**Notes:** Screw terminals (6-65A); 5 mm (80-150A);  
no lugs (185-2000A)

#### Warranties:

- 1 year

#### Specifications:

- **Amperage Rating:** 7A
- **Coil:** 24V 60 Hz
- **Coil Voltage:** 24 Vac, 60 Hz
- **Contact Configuration:** 1NC
- **Frame Size:** 45 mm
- **Frequency Rating:** 60 Hz
- **Max Hp Rating:** 0.25, 1/1.5, 2, 3, 5 (1/3PH  
@120,240/208,240,480,600 V)
- **Number Of Poles:** Three-pole
- **Operation:** Non-reversing
- **Series:** XT IEC series
- **Terminals:** Screw terminals
- **Type:** Full voltage non-reversing contactor
- **Wattage:** 3 kW

#### Supporting documents:

- [Eaton Specification Sheet - DILM7-01\(24V60HZ\)](#)
- [Global Data Sheet - DILM7-01\(24V60HZ\)](#)

#### Certifications:

- EN 60947
- CSA Certified
- IEC 60947
- UL Listed

**Product compliance:**

- RoHS Compliant
- CE Marked

---

© 2016 Eaton. All rights reserved.