

Eaton XT IEC mini contactor

DILM12-10(600V60HZ)

Dimensions:

- **Height:** 2.7 IN
- **Length:** 1.8 IN
- **Width:** 3 IN

Weight: .48 LB

Notes: Screw terminals (6-65A); 5 mm (80-150A);
no lugs (185-2000A)

Warranties:

- 1 year

Specifications:

- **Amperage Rating:** 12A
- **Coil:** 600V 60 Hz
- **Coil Voltage:** 600 Vac, 60 Hz
- **Contact Configuration:** 1NO
- **Frame Size:** 45 mm
- **Frequency Rating:** 60 Hz
- **Max Hp Rating:** 1, 2/ 3, 3, 10, 10 (1/3PH
@120,240/208,240,480,600 V)
- **Number Of Poles:** Three-pole
- **Operation:** Non-reversing
- **Series:** XT IEC series
- **Terminals:** Screw terminals
- **Type:** Full voltage non-reversing miniature
contactor
- **Wattage:** 5.5 kW

Supporting documents:

- [Global Data Sheet - DILM12-10\(600V60HZ\)](#)
- [Eaton Specification Sheet - DILM12-10\(600V60HZ\)](#)

Certifications:

- EN 60947
- IEC 60947
- CSA Certified

- UL Listed

Product compliance:

- CE Marked
- RoHS Compliant

© 2016 Eaton. All rights reserved.