

Thunderbolt 4 Dock, 96W Power Delivery, Single 8K/Dual Monitor 4K 60Hz, 3xTB4/USB4 ports, 4xUSB-A, SD, GbE, Thunderbolt 4 Docking Station for Windows or TB3 MacBook, 0.8m Cable

Product ID: TB4CDOCK



This Thunderbolt 4 Certified docking station lets you use a single Thunderbolt 4, Thunderbolt 3 or USB4 port to add high-performance connectivity and charge your Thunderbolt 4 or USB4 Windows laptop, Thunderbolt 4 M1 Max/M1 Pro MacBook, or your Thunderbolt 3 M1 or Intel MacBook (macOS 11 Big Sur or higher).

For easy deployment the dock includes a 2.6 ft. (0.8 m) Thunderbolt 4 cable that connects to the front-facing host port, and features Kensington-style security slots.

The docking station utilizes the high 40Gbps throughput available from your computer's Thunderbolt 4, Thunderbolt 3, or USB4 port to provide a wide range of port connectivity to suit a variety of applications, including daisy chaining up to five devices from the TB4/USB4 ports.

The dock features:

- 3x downstream Thunderbolt 4/USB4 ports to flexibility connect Thunderbolt 4, Thunderbolt 3, and USB peripheral devices and display(s), with the added benefit of 15W (3A) device charging per each port.
- 3x USB 3.2 Gen 2 (10Gbps) Type-A ports to connect USB peripheral devices.
- 1x USB 2.0 (480Mbps) Type-A port that supports BC 1.2 with 7.5W (1.5A) for charging tablets and smartphones, or connecting USB Human Interface Device(s) (HID), such as a USB transceiver, to minimize signal interference.
- 1x Gigabit Ethernet port with PXE boot and WoL to connect to a wired Local Area Network (LAN).
- 1x Secure Digital (SD) 4.0/UHS-II card reader to externally access SD, SDHC and SDXC memory cards.
- 1x 3.5mm 4-position TRRS Audio Jack to connect a 3.5mm headset.

Up to two monitors can be attached to any of the downstream Thunderbolt 4 ports using USB-C monitors, Thunderbolt monitors or USB-C DP Alt Mode to video adapters (video adapter required, each sold separately).



On Thunderbolt 4 Windows laptops the dock can support dual monitors with resolutions up to 4K 60Hz, or a single monitor with resolutions up to 8K 30Hz, 6K 60Hz, 5K 60Hz, 4K 60Hz.

On Thunderbolt 4 M1 Max and M1 Pro MacBooks the dock can support dual monitors with resolutions up to 4K 60Hz, or a single monitor with resolutions up to 6K 60Hz, 5K 60Hz, 4K 60Hz.

On M1 Thunderbolt 3 MacBooks the dock can support a single monitor with resolutions up to 6K 60Hz, 5K 60Hz, 4K 60Hz.

On Intel Thunderbolt 3 MacBooks the dock can support dual monitors with resolutions up to 4K 60Hz, or a single monitor with resolutions up to 6K 60Hz, 5K 60Hz, 4K 60Hz.

On USB4 Windows laptops the dock can support a single monitor with resolutions up to 8K 30Hz, 6K 60Hz, 5K 60Hz, 4K 60Hz.

The Thunderbolt 4 docking station includes a 135W power adapter and supports 96W USB power delivery. This enables the dock to charge your MacBooks and Thunderbolt 4 and USB4 Windows laptops. Plus, the added power provides downstream TB4/USB4 ports with 15W (3A) for device charging, and enables one of the USB-A ports to support BC 1.2, for charging tablets and smartphones.

To ensure compatibility with your Thunderbolt 4 computers and Thunderbolt 4/3 peripheral devices. This certification provides assurance the dock will be fully compatible with Intel Evo/Tiger Lake (11th gen & up) Thunderbolt 4 laptops including: Dell Precision 5560/5760, XPS 13 9310, HP EliteBook 850 G8, ProBook 450 G8, and Lenovo X1 Carbon 9th Gen. The dock is also compatible with M1 & Intel Thunderbolt 3 MacBooks (11.0 & up).

Developed to improve performance and security, StarTech.com Connectivity Tools is the only software suite on the market that works with a wide range of IT connectivity accessories. The software suite includes:

Advanced Windows Layout Utility: To setup and save custom windows layouts.

Mac Address Pass-Through Utility: To improve network security.

USB Event Monitoring Utility: To track and log connected USB devices

Wi-Fi Auto Switch Utility: Enabling users to quickly access faster network speeds via wired LAN.

For more information and to download the StarTech.com Connectivity Tools application, please visit: www.StarTech.com/Connectivity-Tools

TB4CDOCK is backed by a 3-year StarTech.com warranty, and free lifetime multilingual, North American based technical support.

Certifications, Reports and Compatibility

Applications

- Use in hot-desk workstations for user laptop hoteling
- Charge your tablets and smartphones from the B.C 1.2 USB-A port
- Externally access SD, SDHC and SDXC memory cards



Features

- COMPATIBILITY: Features 3x downstream Thunderbolt 4 (40Gbps) ports to connect TB4, TB3, USB4 & USB 3.2 peripherals & display(s); Compatible w/Windows Thunderbolt 4/USB4 laptops or M1 Max/M1 Pro & Intel Thunderbolt 3 MacBooks (macOS 11 Big Sur or higher)
- CERTIFIED 96W POWER DELIVERY: Charge most laptops including high performance MacBooks and Thunderbolt 4/USB4 Windows laptops; Downstream TB4/USB4 ports support 15W (3A) charging; 1x BC 1.2 USB-A port with 7.5W (1.5A) for charging tablets & smartphones
- PORT FLEXIBILITY: 3x TB4 ports for peripherals, up to 2 extended displays (w/USB-C video adapters), daisy chain up to 5 devices; 4x USB-A ports (3x 10Gbps/1x BC 1.2 fast charge); SD 4.0 card reader; Gigabit Ethernet (w/PXE Boot/WoL); 3.5mm headset port
- DISPLAY COMPATIBILITY: Up to single 8K30Hz/6K60Hz/5K60Hz or dual monitors at 4K60Hz on Thunderbolt 4 or USB4 Windows laptops supporting multiple monitors Single 4K/5K/6K60Hz on M1 MacBooks Dual 4K60Hz/Single 5K/6K on TB3 Intel/TB4 M1 Pro/Max MacBooks
- THUNDERBOLT CERTIFIED: Fully compatible w/Intel Evo, Tiger Lake (11th gen) & up TB4 laptops (Dell Precision 5560/5760, XPS 13 9310, HP EliteBook 850 G8, ProBook 450 G8, Lenovo X1 Carbon 9th Gen); Also compatible w/M1/M1 Max/Pro & TB3 MacBooks (11.0 & up)
- EASY DEPLOYMENT: Dock includes 2.6 ft (0.8 m) Thunderbolt 4 cable; Front host port; Kensington-style security slots; Auto driver setup
- CONNECTIVITY TOOLS: Provided with this docking station, the application improves performance and security, featuring MAC Address Changer, USB Event Monitoring, Windows Layout & Wi-Fi Auto Switch utilities

Hardware		
	Warranty	3 Years
	Fast-Charge Port(s)	Yes
	Displays Supported	2
	Audio	Yes
	Bus Type	Thunderbolt 4
	Compatible Lock Slot	Kensington Mini Slot / Standard Slot
		Kensington Standard Slot (K-Slot)
	Chipset ID	Intel - JHL8440
		Cypress - CYUSB4357
		Parade - FL5801



Parade - FL5801

Cypress - CYPD5235

Realtek - RTL8153B

Realtek - ALC4042

Genesys Logic - GL3226

Performance

Maximum Digital Resolutions

Thunderbolt 4 Windows Systems: Dual 4K 60Hz or Single 8K

30 Hz / 6K 60 Hz / 5K 60 Hz / 4K 60 Hz

Thunderbolt 4 M1 Pro & M1 Max Mac Systems: Dual 4K 60Hz or Single 5K 60Hz / 4K 60Hz, Thunderbolt 3 Intel Mac Systems: Dual 4K 60Hz or Single 6K 60Hz / 5K 60Hz / 4K 60Hz,

Thunderbolt 3 M1 Mac Systems: Single 4K 60Hz or 6K 60Hz /5K 60Hz / 4K 60Hz, Thunderbolt 4 & Compatible USB4 Systems: Dual 4K 60Hz or Single 8K 30Hz / 6K 60Hz / 5K 60Hz / 4K 60Hz

USB4 Systems: Single 8K 30Hz / 6K 60Hz / 5K 60Hz / 4K 60Hz

<i>USB4 Windows laptops may support dual-displays over Thunderbolt if supported by the USB4 Windows Laptop</i>

Audio Specifications

Analog Stereo - 2 Channel Audio

Memory Media Type

SD/MMC (Secure Digital/Multimedia Card)

SDHC (Secure Digital High Capacity)

SDXC (Secure Digital eXtended Capacity)

microSD (Micro Secure Digital) (adapter required)

microSDHC (Micro Secure Digital High Capacity) (adapter

required)

microSDXC (Micro Secure Digital eXtended Capacity) (adapter

required)

Compatible Networks

10/100/1000 Mbps

Auto MDIX

Yes

PXE

Yes

Full Duplex Support

Yes

Connector(s)



External Ports SD Slot

USB 2.0 A (Fast-Charge, 4 pin)

3.5mm Audio (4-Position, Speakers + Mic, CTIA)

Thunderbolt 4 (USB 4.0)

Ethernet Gigabit

USB 3.1 USB Type-A (9 pin, Gen 2, 10 Gbps)

Host Connectors Thunderbolt 4 (USB 4.0)

Software

OS Compatibility Windows 11

Windows 10

macOS Big Sur (11.0)

macOS Monterey (12.0)

Special Notes / Requirements

Note The docking station is compatible with Thunderbolt 4/USB4

Windows laptops, Thunderbolt 4 M1 Max/M1 Pro MacBooks, and Thunderbolt 3 M1/Intel MacBooks (macOS 11 Big Sur or higher)

Indicators

LED Indicators White On: Power

Green On: Connected to Host

Power

Power Source AC Adapter Included

Input Voltage 100 - 240 AC

Input Current 2.5 A

Output Voltage 20V DC

Output Current 6.75 A

Center Tip Polarity Positive

Plug Type 7.4mm OD, 5.5mm ID, 0.5mm CPD



Power Consumption (In

Watts)

135

Environmental

Operating Temperature 0 to 50C

Storage Temperature -20 to 70C

Humidity 0% to 95% (non-condensing) at 25C

Physical Characteristics

> Color Black & Gray

Material Aluminum and Plastic

Cable Length 31.5 in [80 cm]

Product Length 3.3 in [83.7 mm]

Product Width 7.6 in [19.4 cm]

Product Height 1.1 in [29.0 mm]

Weight of Product 35.3 oz [1000.0 g]

Packaging Information

> Package Length 5.7 in [14.5 cm]

> Package Width 9.3 in [23.5 cm]

Package Height 3.5 in [90.0 mm]

Shipping (Package)

Weight

2.4 lb [1.1 kg]

What's in the Box

Included in Package Thunderbolt 4 Docking Station

Thunderbolt 4 Cable

Universal Power Adapter (NA/JP)

Quick-Start Guide

^{*}Product appearance and specifications are subject to change without notice.