

PSEN cs1.1p 1 switch

540050



RFID safety switch 2 safe SC outputs, 8-pin M12 male connector, 4 actuation directions, support for SDD, IP67, switching distance 21 mm, Sao = 15 mm, Sar = 40 mm, PU = 1 piece coded switch without actuator.

Technical details

General data	
Approval:	CE, cULus Listed, FCC, IC, EAC (Eurasian), TÜV
Sensor principle:	Transponder
Coding level to ISO 14119:	Low
Classification to EN 60947-5-3:	PDDB
Transponder coding:	coded
Suitable for series connection:	yes
unit type:	Sensor
Technical data	
Electrical data	
Supply voltage (V):	24 - 24 V
Type of supply voltage U1:	DC
Power consumption DC:	2 W
Inputs	
Number of inputs:	2
DC voltage at input:	24 V DC
Semiconductor outputs	
Number of OSSD outputs:	2
Number of sig. outputs:	1
Potential isolation S/C O:	No

S/C output short circuit proof:	Yes
Utilisation cat. to EN 60947-1:	DC-12
Environmental data	
Ambient temperature standard:	EN 60068-2-14
Ambient temperature:	-25 - 70 °C
Storage temperature standard:	EN 60068-2-1/-2
Climatic suitability standard:	EN 60068-2-78
Humidity rating:	93 % r. h. at 40 °C
EMC to standard ...:	EN 60947-5-3
Vibration to standard ...:	EN 60947-5-2
Acc. shock to standard1:	30g
Overvoltage category:	III
Pollution degree clear.&creep.:	3
Switching distances	
Change op. dist. temp.change:	+/-0.01mm/°C
Mechanical data	
Type 1 actuator:	PSEN cs1.1
Sensor can be flush-mounted:	Yes, follow installation guide
Connection type:	M12, 8-pin male
Housing material upper part:	PBT
Height dimension:	75 mm
Width dimension:	40 mm
Depth dimension:	40 mm
Net weight:	123 g
Gross weight:	154 g
Transponder	
Operating frequency:	122 kHz - 128 kHz

Obligatory accessories



540080

PSEN cs1.1 1 actuator

Optional accessories



540324

PSEN cable angle M12 8-pole 10m



540325

PSEN cable angle M12 8-pole 30m



540326

PSEN cable axial M12 8-pole 30m



540338

PSEN Y junction M12-M12/M12 PIGTAIL



540320

PSEN cable axial M12 8-pole 5m



540331

PSEN T junction (auxiliary contact) M12



540342

PSEN cable M12-8sf M12-8sm, 10m

	540343	PSEN cable M12-8sf M12-8sm, 20m
	540321	PSEN cable axial M12 8-pole 10m
	540322	PSEN cable angle M12 8-pole 3m
	540344	PSEN cable M12-8sf M12-8sm, 30m
	540333	PSEN cable M12-8sf, 20m
	540323	PSEN cable angle M12 8-pole 5m
	540319	PSEN cable axial M12 8-pole 3m
	540130	SDD ES ETH
	540340	PSEN cable M12-8sf M12-8sm, 2m



540341

PSEN cable M12-8sf M12-8sm, 5m



540132

SDD ES PROFIBUS



773603

PDP67 F 4 code
