




Made in the United States of America



D-Ring for Adjustability

Red Elastic Strap for High Visibility

2-Layer Rubber Sole

24" Conductive Ribbon

The HGS1MD-RED heel grounder features a D-Ring Strap and elastic hook and loop for adjustability. Compliance verification is simplified by the bright red elastic strap. Heel Grounders are designed and manufactured for comfort, durability and cost effectiveness.

Properties	Typical Value	Test Method
Hook and Loop	3/4"	
Elastic Strap	Red	
Sole Interior	Non-marking	
Sole Exterior	<10 ⁵ ohms	
Total Grounder	1.0 x 10 ⁶ ohms	ANSI/ESD S20.20, EIA 625 ESD-SP9.2

Item	Description
HGS1MD-RED	Red Standard Heel Grounder, 1 Megohm Resistor

Note: This product is not recommended for use on equipment with operating voltage exceeding 250 VAC.

CAUTION: The ESD Series is for electrostatic control. It will not reduce or increase your risk of receiving electric shock when using or working on electrical equipment. Follow the same precautions you would use without wrist straps, including:

- Make certain that equipment having a grounding type plug is properly grounded.
- Make certain that you are not in contact with grounded objects other than through the ESD Series.

Unless otherwise noted, tolerance ± 10%

Specifications and procedures subject to change without notice.

HGS1MD-RED - STANDARD HEEL GROUNDER, D-RING, RED ELASTIC

926 JR Industrial Drive, Sanford, NC 27332
WEB SITE: StaticControl.com
PHONE (919) 718-0000

DRAWING NUMBER
HGS1MD-RED

DATE
August 2015

