


IEEE1355 CABLING



	J1	Wire color	J2
✕	2-e	Brown	1-a
✕	1-e	Blue	2-a
✕	2-d	Red	1-b
✕	1-d	Green	2-b
✕	2-c	Black	2-c
✕	1-c	White	1-c
✕	2-b	Orange	1-d
✕	1-b	Yellow	2-d
✕	2-a	Violet	1-e
✕	1-a	Grey	2-e
	Shell	Braid	Shell

NOTES /

- 1.) MECHANICAL REQUIREMENTS
  - OPERATING TEMPERATURE = -20° TO +80°C
  - MATING CYCLES : 250, PERFORMANCE LEVEL 2 ( IEC 60512-5 )
- 2.) THE CONNECTOR COMPLIES REQUIREMENT : IEC 61076-4-107
- 3.) WHITE LABEL INFORMATION:
 

DATE CODE & LOT INFORMATION  
HARTING P/N
- 4.) CABLE MUST BE PERFORMED HI-POT TEST AND CONTINUITY TEST

33 27 243 500 0018	5 m												
33 27 243 200 0017	2 m												
33 27 243 100 0016	1 m												
33 27 243 050 0015	0.5 m												
<i>Part-No.</i>	<i>Dim. L</i>												
All Dimensions in mm Original Size MM A 3	Techn. Character. <table border="1"> <tr> <td></td> <td>Det.</td> <td>Name</td> </tr> <tr> <td>Detail.</td> <td>06.05.08</td> <td>J.S.</td> </tr> <tr> <td>Insp.</td> <td></td> <td></td> </tr> <tr> <td>Stand.</td> <td></td> <td></td> </tr> </table>		Det.	Name	Detail.	06.05.08	J.S.	Insp.			Stand.		
		Det.	Name										
	Detail.	06.05.08	J.S.										
	Insp.												
Stand.													
Free size tolerances	Har-link male DE IEEE1355 cabling double shielded cable assembly, **m												
Scale		/											
ZHANGHAI HARTING LIMITED													
Mod.	Dat.	Name	TB 33 27 24x xxx 00xx Sub.	Page									