



TOLERANCE FOR "L" LENGTH

| DIMENSION RANGE | TOLERANCE |
|-----------------|-----------|
| 0.0m - 1.0m | +10/0 mm |
| >1.0m - 3.0m | +30/0 mm |
| >3.0m - 5.0m | +50/0 mm |
| >5.0m - 10.0m | +100/0 mm |
| >10.0m | +200/0 mm |

NOTES:

- 1) CABLE MUST BE PERFORMED 100% CONTINUITY TEST.
- 2) WHITE LABEL CONTENT:

CMK/YR-XXXXX-X-XX
HARTING P/N

BLACK FONT, FONT HEIGHT: 3.5.

- 3) CABLE SHOULD BE FOLDED MANY CIRCLES ACCORDING TO TOTAL CABLE LENGTH AND PACKED BY A PLASTIC BAG (QTY ACCORDING TO ACTUAL CONDITION),STICK THE LABEL WITH P/N,QTY AND LOT NUMBER ON IT,THEN PUT IT INTO THE CARTON (QTY ACCORDING TO ACTUAL CONDITION).
- 4) THE CARTON SHOULD BE STICKED THE LABEL WITH P/N AND QTY CONTENT.

| | |
|--------------------|-------|
| 33 18 243 100 0067 | 1 m |
| 33 18 243 080 0066 | 0.8 m |
| 33 18 243 050 0065 | 0.5 m |
| 33 18 243 020 0064 | 0.2 m |
| 33 18 243 010 0063 | 0.1 m |

Part-No.



Techn Character:

free size tolerances

| Mod. | Doc. | Name | Scale | Free size tolerances |
|------|------|----------------------|-------|---|
| | | ZHAI HARTING LIMITED | / | SEK 10P FEMALE DOUBLE END FLAT CABLE ASSEMBLY.L=MM |
| | | | | TB 33 18 243 xxx 00xx |