



Datasheet White Coated Steel Spring Clip

RS Stock number 507-832



Description:

White or black plastic coated spring clips (tool clips) available in a range of sizes.

Nylon coated steel gives excellent scratch protection

Temperature range: 0°C to 60°C

Ideal for use as tool retaining clips etc

Clips are supplied with fixing screws

Available in individual sizes, or as a kit of 306 assorted clips with black finish (RS stock no. 291-830)

Kit Contents										
Clip Size (in.)	1/4	3/8	1/2	5/8	3/4	1	1 1/8	1 1/4	1 1/2	
Quantity	48	48	48	34	20	36	30	24	18	

Specifications:

Clip Diameter: 6.35 mm
Depth: 15.08 mm
Fixing Hole Diameter: 8BA
Height: 6.35 mm
Material: 5teel
Overall Width: 13.49 mm
Vinyl Coating Colour: Black


RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.



SPRING STEEL TOOL CLIPS

ENGLISH





GENERAL TOOL AND FLUORESCENT LIGHTING FITTING CLIPS

L.S. 101 Series. A range of sizes to grip diameters 1/4'' - 2'' (6.35mm - 50.8mm) Standard Finish: - K and S. Polythene coating colours: - Black, White.

RS STOCK NUMBER	Nominal Size ins <i>mm</i>	A ins <i>mm</i>	B ins <i>mm</i>	C ins <i>mm</i>	E ins <i>mm</i>	H BA Clearance	W ins <i>mm</i>	T ins <i>mm</i>
507-832	1/4 <i>6.35</i>	13/64 5.16	25/64 9	17/32 13.49	19/32 <i>15.08</i>	8	1/4 <i>6.3</i> 5	.0148 . <i>376</i>
507-826	3/8 <i>9.53</i>	19/64 <i>7.54</i>	3/8 <i>9.53</i>	5/8 15.88	25/32 19.84	8	1/4 <i>6.35</i>	.0164 .419
507-810	1/2 12.7	13/32 10.32	15/32 <i>11.91</i>	53/64 21.03	31/32 <i>24.61</i>	6	5/16 <i>7.94</i>	.018 .457
507-804	5/8 15.88	1/2 <i>12.7</i>	35/64 1 <i>3.89</i>	31/32 <i>24.61</i>	1.5/32 <i>29.37</i>	6	5/16 <i>7.94</i>	.022 .558
507-797	3/4 19.05	39/64 15.48	41/64 16.27	1.1/8 <i>28.58</i>	1.3/8 <i>34.93</i>	4	5/16 <i>7.94</i>	.024 .610
507-781	1 25.4	3/4 19.05	25/32 19.84	1.3/16 <i>30.16</i>	1.5/8 <i>41.28</i>	4	5/16 <i>7.94</i>	.022 .558
507-775	1.1/8 28.58	29/32 23.02	29/32 23.02	1.9/16 <i>39.69</i>	1.15/16 <i>49.21</i>	4	3/8 <i>9.53</i>	.028 .711
507-769	1.1/4 <i>31.75</i>	1.1/64 <i>25.8</i>	1 <i>25.4</i>	1.45/64 <i>43.26</i>	2.1/8 <i>53.98</i>	4	7/16 11.11	.032 .813
507-753	1.1/2 <i>38.1</i>	1.7/32 <i>30.96</i>	1.3/16 <i>30.16</i>	2 50.8	2.1/2 <i>63.5</i>	4	1/2 12.7	.036 <i>.91</i>
	2 50.8	1.9/16 <i>39.69</i>	1.5/8 <i>41.28</i>	2.1/4 <i>57.15</i>	3.1/8 <i>79.38</i>	4	1/2 12.7	.036 <i>.910</i>
	7/8 22.22	53/64 21	3/4 19.05	1.1/8 <i>28.5</i>	1.15/32 <i>37.3</i>	4	5/16 <i>7.94</i>	

^{*101/19 - 2} holes in base at 12.75mm centres.

N.B: THESE DIMENSIONS ARE FOR UNCOATED CLIPS.

Finishes: - K = Electro-plated zinc.

Colourless/clear, chromate passivation.

S = Polythene coated.