



THESE DRAWINGS ARE THE PROPERTY OF QUALTEK ELECTRONICS AND NOT TO BE REPRODUCED FOR OR COMMUNICATED TO A THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF AN OFFICER OF QUALTEK ELECTRONICS.


	Revision				
Rev.	Description	Date	Approved		














## **CONTROLLED**

5	Cover back of the body, NYLON Black Color	1				
4	Contact PIN Brass Strip t=0.7mm Tin Plated	1				
3	Contact PIN Brass Strip t=0.7mm Tin Plated	1				
2	Contact PIN Brass Strip t=0.7mm Tin Plated	1				
1	Body Insulator NYLON Black Color	1				

Dim range	Tolerance +/-	Qual	tek Electronics Corp.  PPC DIVISION		
(mm)	(mm)	Part Number: 739W-X2/30 RoHS Compliant			
0-1	0.15	7 3 7 1 7 12 7 3 0 Compliant			
1-6	0.20	Description: SNAP-IN 20 AMP T-SLOT RECEPTACLE			
6-18	0.30				
18-50	0.50		UNIT: mm		
50-120	0.70				
		Drawn / Date	Checked / Date	Approved / Date	
120-250	0.90	D.Povozhaev	05-14-07	JJH / 05-14-07	
250-500	1.20	05-14-07			

## NOTE:

RATING: 20A 125V AC

RECOMMENDED TO USE SOLID WIRE ONLY

PANEL THICKNESS: 0.8~1.8mm

APPROVALS: UL, cUL RoHS COMPLIANT