

8701

THREADLOCKER, LOW STRENGTH, REMOVABLE

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: 8701**Other Means of Identification:** Threadlocker, Low Strength, Removable**Related Part #:** 8701-10ML, 8701-50ML

Recommended Use and Restriction on Use

Use: Removable thread locker for fasteners up to ¼"**Uses Advised Against:** Not available

Details of Manufacturer or Importer

ManufacturerMG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADAMG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA**TEL** +1-800-340-0772**FAX** +1-800-340-0773**E-MAIL** support@mgchemicals.com**WEB** www.mgchemicals.com**TEL** +1-905-331-1396**FAX** +1-905-331-2682**E-MAIL** info@mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number


For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA—Call CHEMTREC at **+1-800-424-9300****For emergencies involving the transport of dangerous goods;** 24/7 service
CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

8701
THREADLOCKER, LOW STRENGTH, REMOVABLE
Section 2: Hazard(s) Identification
Classification of the Chemical Material
GHS Categories

Criteria		Category	Signal Word	Pictograms
Sensitization	Skin	1	Warning	Exclamation
Eye Irritation		2	Warning	Exclamation
Skin Irritation		2	Warning	Exclamation
Specific Target Organ Toxicity	Single Exposure	3	Warning	Exclamation
Hazardous to the Aquatic Environment	Chronic	3	None	None

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	WARNING
Pictograms	Hazard Statements
	H319: Causes serious eye irritation H335: May cause respiratory irritation H315: Cause skin irritation H317: May cause an allergic skin reaction
<i>No symbol mandated</i>	H412: Harmful to aquatic life with long lasting effects
Prevention	Precautionary Statements
P102	Keep out of reach of children.
P261	Avoid breathing mist, vapors.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, eye protection.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.

Section continued on the next page

8701
THREADLOCKER, LOW STRENGTH, REMOVABLE
Continued...

Response	Precautionary Statements
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical attention.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
Storage	Precautionary Statements
P403 + P233	Store in well-ventilated area. Keep container tightly closed.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents/container in accordance to local, regional, international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	% Weight
25852-47-5	polyglycol dimethacrylate	50-60%
9004-96-0	polyglycol oleate	20-30%
81-07-2	saccharin	1-5%
112945-52-5	silica, amorphous fumed	1-5%
57-55-6	1,2-propylene glycol	1-3%
80-15-9	cumene hydroperoxide	1-3%
13463-67-7	titanium dioxide	0.5-1.5%

8701**THREADLOCKER, LOW STRENGTH, REMOVABLE****Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>redness, severe irritation, pain</i>
Response	Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
IF INHALED	P304 + P340, P312
Immediate Symptoms	<i>cough, irritation of the respiratory track</i>
Delayed Symptoms	<i>(extreme exposure) shortness of breath, wheezing</i>
Response	Remove person to fresh air and keep comfortable for breathing. If feeling unwell: Call a POISON CENTER/doctor.
IF ON SKIN	P303 + P352, P362 + P364, P333 + P313
Immediate Symptoms	<i>mild to moderate irritation, redness</i>
Response	Wash with plenty of water/shower. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
IF SWALLOWED	P301 + P330 + P331
Immediate Symptoms	<i>abdominal pain, burning sensation</i>
Response	Rinse mouth. Do not induce vomiting. Call a POISON CENTRE/doctor if you feel unwell.

Section 5: Fire-Fighting Measures

Extinguishing Media	Use dry chemical, carbon dioxide, or chemical foam to extinguish. Use water spray to cool containers.
Specific Hazards	Will burn if involved in a fire. Produces irritating fumes in fires or in contact with hot surfaces.
Combustion Products	Produces carbon oxides (CO, CO ₂), nitrogen oxides (NO _x), and silicon oxides
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

8701**THREADLOCKER, LOW STRENGTH, REMOVABLE****Section 6: Accidental Release Measures**

Personal Protection	See personal protection equipment in Section 8.
Precautions for Response	Avoid breathing the vapors/fumes.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
Containment Methods	Remove all sources of ignition. Prevent spill from entering drains and waterways. Contain with inert absorbent (such as soil, sand, vermiculite).
Cleaning Methods	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.
Disposal Methods	Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention	Keep out of reach of children. Contaminated work clothing should not be allowed out of the workplace. Take off contaminated clothing and wash it before reuse. Keep away from heat. Avoid breathing mist, vapors. Use only outdoors or in a well-ventilated area.
Handling	Wear protective gloves, eye protection. Wash hands thoroughly after handling.
Storage	Protect from sunlight. Do not expose to temperatures exceeding 38 °C [100 °F]. Store in a well-ventilated area. Keep tightly closed. Store locked up.

8701

THREADLOCKER, LOW STRENGTH, REMOVABLE

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country or Vendor	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
1,2-propylene glycol	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	Not established	Not established
	Canada AB	Not established	Not established
	Canada BC	Not established	Not established
	Canada ON	50 ppm	Not established
	Canada QC	Not established	Not established
titanium dioxide	ACGIH	10 mg/m ³	Not established
	U.S.A. OSHA PEL	15 mg/m ³	Not established
	Canada AB	10 mg/m ³	Not established
	Canada BC	10 mg/m ³	Not established
	Canada ON	10 mg/m ³	Not established
	Canada QC	10 mg/m ³	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA, and Canadian provinces exposure limits were consulted. Limits from the RTECS database² and from suppliers' SDSs were also consulted. Short term exposure limits (STEL) are usually for 15 min and long term permissible exposure limits (PEL) for 8 h.

Engineering Controls

Ventilation Keep airborne concentrations below the occupational exposure limits (OEL).

Personal Protective Equipment

Eye protection Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Use safety glasses with lateral protection.

Skin Protection Wear appropriate protective clothing to prevent skin contact.

RECOMMENDATION: Use polyethylene gloves or other chemically resistant gloves.

Section continued on the next page

8701

THREADLOCKER, LOW STRENGTH, REMOVABLE

Respiratory Protection If exposed to mist, wear respirator such as a half-mask respirator.

RECOMMENDATION: Consult your local safety supply store to ensure your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in section 3 of this SDS, and that the respirator is fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	Not available
Appearance	Purple	Upper Flammability Limit	Not available
Odor	Mild	Vapor Pressure @27 °C	<5 mmHg [<0.7 kPa]
Odor Threshold	Not available	Vapor Density	>2.6 (Air =1)
pH	Not available	Relative Density @21 °C	1.05
Freezing/Melting Point	Not available	Solubility in Water	Slight
Initial Boiling Point	≥149 °C [≥300 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point	>93 °C [>200 °F]	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability (solid, gas)	Not applicable	Viscosity @40 °C	Not available

8701**THREADLOCKER, LOW STRENGTH, REMOVABLE****Section 10: Stability and Reactivity**

Reactivity	Not available.
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Temperatures over 38 °C [100 °F] and incompatible substances
Incompatibilities	Strong oxidizing agents, strong acids, strong bases, alkali or alkali earth metals
Polymerization	Will not occur
Decomposition	At 70 °C [158 °F], the cumene hydroperoxide may undergo self-accelerating decomposition. For thermal decomposition, see combustion products in Section 5.

Section 11: Toxicological Information**Summary of Effects and Symptoms by Routes of Exposure**

Eyes	Causes severe eye irritation if splashed in eyes or exposed to vapors. May also cause eye redness or pain.
Skin	May cause mild to moderate skin irritation.
Inhalation	May cause nose, throat and lung irritation.
Ingestion	It may cause irritation and burning sensation. (See inhalation symptoms.)
Chronic	Prolonged and repeated exposure may damage mucous tissue in the upper respiratory tract and lungs. Long term exposure to titanium dioxide dust or mist may cause cancer. Prolonged and repeated exposure may lead to skin sensitization.

Section continued on the next page

8701

THREADLOCKER, LOW STRENGTH, REMOVABLE

Lethal Exposure Concentrations

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation	TCLo inhalation
polyglycol dimethacrylate	Not available	Not available	Not available	Not available
polyglycol oleate	>5 g/kg Rat	Not available	Not available	Not available
saccharin	17 000 mg/kg Rat	Not available	Not available	Not available
silica, amorphous fumed	3 160 mg/kg Rat	Not available	Not available	Not available
1,2-propylene glycol	>20 g/kg Rat	>29 800 mg/kg Rabbit	Not available	Not available
cumene hydroperoxide	382 mg/kg Rat	490 mg/kg Rabbit	220 ppm Rat	Not available
titanium dioxide	60 g/kg Rat	Not available	Not available	Not available

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier SDSs were also consulted.

Other Toxicological Effects

Skin corrosion/irritation	Moderate skin irritant.
Serious eye damage/irritation	Serious to moderate eye irritant
Respiratory and skin sensitization (allergic reactions)	Skin sensitizer based on animal studies on components

Section continued on the next page

8701**THREADLOCKER, LOW STRENGTH, REMOVABLE****Carcinogenicity**
(risk of cancer)

This anaerobic adhesive mixture has fast fixture time in contact with air and polymerizes in a few minutes only. Therefore, the mixture doesn't give rise to carcinogen category 2 hazard because the titanium dioxide content is inextricably bound in the quick forming polymer matrix and is not bioavailable in a long term or repeated exposure under normal use or foreseeable emergencies.

Titanium Dioxide [13463-67-7]

IARC Group 2B: Possibly carcinogenic to humans

ACGIH A4: Not classified as a human carcinogen

CA Prop 65: Listed as a carcinogen

NTP: Not listed

Mutagenicity
(risk of heritable genetic effects)

Based on available data, the classification criteria are not met.

Reproductive Toxicity
(risk to sex functions)

Based on available data, the classification criteria are not met.

Teratogenicity
(risk of fetus malformation)

Based on available data, the classification criteria are not met.

STOT-single exposure

Respiratory irritant effects

STOT-repeated exposure

This anaerobic adhesive mixture has a fast fixture time in contact with air and polymerizes in a few minutes only. The mixture doesn't give rise to STOT RE 2 hazard because the cumene hydroperoxide content is inextricably bound in the quick forming polymer matrix and, therefore, is not bioavailable in a long term or repeated exposure under normal use or foreseeable emergencies.

Cumene hydroperoxide is a STOT RE 2 and causes damage to lungs through prolonged or repeated exposure. Overexposure may lead to pulmonary edema.

Aspiration hazard

Based on available data, the classification criteria are not met. The liquid content is not an aspiration hazard.

8701**THREADLOCKER, LOW STRENGTH, REMOVABLE****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Cumene hydroperoxide is an acute category 2 environmental toxicant (with minimal LC50 of 3.96 mg/L for *Oncorhynchus mykiss* (rainbow trout); EC50 18.84 mg/L 48 h *Daphnia magna* (water flea); 3.1 mg/L 72 h *Desmodesmus subcapitata*).

Polyglycol dimethacrylate is a class 3 chronic environmental pollutant accord to the predominant classification.

Saccharin, silica, and 1,2-propylene glycol are non-hazardous for the environment for according to GHS classification criteria.

Acute Ecotoxicity

Category 3

Harmful to aquatic life with long lasting effects

Avoid release to the environment.

Chronic Ecotoxicity

Not classifiable

Persistence and Biodegradability

Not available

Bioaccumulative Potential

Not available

Mobility in Soil

Not available

Other Effects

Not available

Section 13: Disposal Considerations

Dispose of contents in accordance with all local, regional, national, and international regulations.

8701**THREADLOCKER, LOW STRENGTH, REMOVABLE****Section 14: Transport Information****Ground**

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations);
USA DOT 49 CFR (Parts 100 to 185) **Regulations.**

Not Regulated

Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Not Regulated

Sea

Refer to IMDG regulations.

Not Regulated

Section 15: Regulatory Information**Canada****Domestic Substance List (DSL)/Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL/NDSL.


Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

Section continued on the next page

8701**THREADLOCKER, LOW STRENGTH, REMOVABLE****USA****Other Classifications****HMIS® RATING**

HEALTH:	* 1
FLAMMABILITY:	1
PHYSICAL HAZARD:	1
PERSONAL PROTECTION:	

NFPA® 704 CODES

Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains cumene hydroperoxide (CAS# 80-15-9; reportable quantity = 10 lb), which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

This product contains saccharin (CAS# 81-07-2; reportable quantity 100 lb), which is subject to the CERCLA reporting requirements of section 102(a).

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity)

This product does titanium dioxide, which is listed as a carcinogenic substances when airborne, as unbound particles of respirable size.

Section continued on the next page

8701**THREADLOCKER, LOW STRENGTH, REMOVABLE****Europe****RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information**SDS Prepared by** Regulatory Department**Date of Revision** 12 December 2018**Supersedes** 07 May 2015**Reason for Changes:** Minor format changes throughout the SDS.**Reference**

1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Section continued on the next page

8701**THREADLOCKER, LOW STRENGTH, REMOVABLE****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
NOELR	No observable effect loading ratio
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer This material safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.