

Torque screwdriver - TSD-M 6NM - 1212226

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 3 - 6 Nm

Your advantages

- ✔ High-precision, finely adjustable torque screwdrivers according to EN ISO 6789
- ✔ TSD-M ... torque screwdrivers are adjustable from 3.0 - 6.0 Nm
- ✔ Torque screwdrivers with hexagonal fast connection holder

Key Commercial Data

| | |
|--------------|---|
| Packing unit | 1 pc |
| GTIN |  4 046356 455572 |
| GTIN | 4046356455572 |

Technical data

Dimensions

| | |
|-----------------|---------|
| Length (b) | 152 mm |
| Width (a) | 37.5 mm |
| Height (c) | 100 mm |
| Blade thickness | 0 mm |
| Blade width | 0 mm |

General

| | |
|-------|-------|
| Color | black |
|-------|-------|

Environmental Product Compliance

| | |
|---------------------------|---|
| California Proposition 65 | Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration |
|---------------------------|---|

Approvals

Approvals

Torque screwdriver - TSD-M 6NM - 1212226


Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|---|--------------------------|
| EAC |  | RU x- DE.xx08.B.02974 |
|-----|---|--------------------------|

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>