



NT-MIL-3/8-0-SP Product Details
[Share](#) | [Print](#) | [Email](#)

NT-MIL-3/8-0-SP

 TE Internal Number: F24044-000
 **Active**
Heat Shrink Tubing

 Converted to EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Heat Shrinkable Tubing
- Product Name = NT-MIL
- Product Source = U.K., U.S.
- Flexible
- Medium Wall Style

[View all Features](#)
Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) | [Request Sample](#) | [Find Similar Products](#) | [Buy Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • Flexible, Rugged, Modified Elastomeric Heat-Shrinkab... (PDF, English) <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Product Type = Heat Shrinkable Tubing • Color = Black <p>Dimensions:</p> <ul style="list-style-type: none"> • Expanded ID, Min. (mm [in]) = 9.53 [0.375] • Recovered ID, Max. (mm [in]) = 5.40 [0.213] <p>Body Features:</p> <ul style="list-style-type: none"> • Product Name = NT-MIL • Pliancy = Flexible • Wall Style = Medium • Wall Type = Single • Material = Chlorinated Polyolefin • Shrink Ratio = 1.75:1 • Fluid Type = Aviation Fuel, Chemicals/Solvents, Ground Vehicle Fuels, Hydraulic Fluid, Lubricating Oil, Water • Resistant To = Abrasion, Fluids, Strain • Wall Thickness - Full Recovery (Nominal) (mm [in]) = 1.01 [0.0397] <p>Housing Features:</p> <ul style="list-style-type: none"> • Material Systems = No <p>Industry Standards:</p> <ul style="list-style-type: none"> • Government/Industry Qualification = Yes • Government/Industry Part Number = M23053/2-202-0, M23053/1-102-0 • Flammability Rating Type = Flame-Retardant • UL Rating = None • CSA Certified = No • Approved Standards = SAE AMS-DTL-23053/1 Class 1 & 2 • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Not relevant for lead free process • RoHS/ELV Compliance History = Converted to comply with RoHS directive 	<p>Environmental:</p> <ul style="list-style-type: none"> • Fluid Resistance = Splash Protection • Operating Temperature (°C) = -70 - +121 <p>Conditions for Usage:</p> <ul style="list-style-type: none"> • Full Recovery Temperature (°C) = 135 • Shrink Temperature, Min. (°C) = 90 • High Temperature Compatible = No <p>Operation/Application:</p> <ul style="list-style-type: none"> • Application = Cable Bundling, Cable Jacketing, Insulation and Protection • Emission Free = No • Product Use = Cable Harnesses, Wire Bundles <p>Packaging Features:</p> <ul style="list-style-type: none"> • Packaging Method = Spool <p>Product Availability:</p> <ul style="list-style-type: none"> • Product Source = U.K., U.S. <p>Other:</p> <ul style="list-style-type: none"> • Brand = Raychem