


DYNAMIC SILENCER MW SPL




Code	A
W0970530062U	1/8 NPT
W0970530063U	1/4 NPT
W0970530064U	3/8 NPT
W0970530065U	1/2 NPT
W0970530066U	3/4 NPT
W0970530067U	1 NPT

SILENCER MW SPL-F




Code	A
W0970530072U	1/8 NPT
W0970530073U	1/4 NPT
W0970530074U	3/8 NPT
W0970530075U	1/2 NPT

SILENCED EXHAUST REGULATOR MW SVE




	Code	A	F	L	CH
Materials:	W0970520001	BSPP 1/8	0.26	0.75 - 0.90	0.81 (13 mm)
Nickel-plated brass	W0970520002	BSPP 1/4	0.30	0.82 - 0.96	0.59 (15 mm)
Sintered nickel-plated bronze	W0970520003	BSPP 3/8	0.38	0.92 - 1.16	7/8 (22 mm)
Stainless steel spring	W0970520004	BSPP 1/2	0.41	0.90 - 1.10	7/8 (22 mm)
	W0970520005	BSPP 3/4	0.47	1.14 - 1.38	1.18 (30 mm)
Features:	W0970520006	BSPP 1	0.54	1.06 - 1.34	1.41 (36 mm)
Pmax: 174 psi					
Temp.: from 14° to 176 °F					

SILENCED EXHAUST REGULATOR MW SVL




Code	A
W0970520010U	M5
W0970520011U	1/8 NPT
W0970520012U	1/4 NPT
W0970520013U	3/8 NPT
W0970520014U	1/2 NPT
W0970520015U	3/4 NPT
W0970520016U	1 NPT

EXHAUST REGULATOR MW DSN



	Code	A	B	CH	CH1
Materials:	W0970520021	BSPP 1/8	BSPP 1/8	0.47 (12 mm)	0.47 (12 mm)
Nickel-plated brass	W0970520022	BSPP 1/4	BSPP 1/8	0.55 (14 mm)	5/8 (16 mm)
	W0970520023	BSPP 3/8	BSPP 1/4	3/4 (19 mm)	0.67 (17 mm)
	W0970520024	BSPP 1/2	BSPP 1/4	0.94 (24 mm)	7/8 (22 mm)
Features:					
Pmax: 174 psi					
Temp.: from 14° to 176 °F					

EXHAUST REGULATOR MW DSE



	Code	A	F	L	CH
Materials:	W0970520031	BSPP 1/8	0.29	0.66 - 0.79	0.55 (14 mm)
Nickel-plated brass	W0970520032	BSPP 1/4	0.39	0.85 - 1.14	3/4 (17 mm)
Features:					
Pmax: 174 psi					
Temp.: from 14° to 176 °F					