



# **Product Description**

Security & Sound Cable, Riser-CMR, 4-18 AWG stranded bare copper conductors with polyolefin insulation, Beldfoil® shield and PVC jacket with ripcord

# **Technical Specifications**

### **Physical Characteristics (Overall)**

Condu	ctor		
AWG	Stranding	Material	No. of Conductors
18	7x26	BC - Bare Copper	4
Conductor Count:			
Conductor Size:			

#### Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.008 in

#### Color Chart

#### **Outer Shield Material**

Туре	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Таре	Aluminum/Polyester	Beldfoil®	100 %	TC - Tinned Copper	24	7x32

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.188 in	0.017 in	Yes

### **Construction and Dimensions**

Cobling		
Cabling		
_eft Hand 4 twist/ft		
ectrical Character	istics	
	istics	
Conductor DCR		
	Nominal Outer Shi	ield DCR
Nominal Conductor DCR	Nominal Outer Shi 7.2 Ohm/1000ft	ield DCR
Nominal Conductor DCR 6.5 Ohm/1000ft		ield DCR
Nominal Conductor DCR 6.5 Ohm/1000ft Capacitance	7.2 Ohm/1000ft	
Nominal Conductor DCR 6.5 Ohm/1000ft Capacitance	7.2 Ohm/1000ft	Nom. Capacitance Conductor to Other Conductor to Shield

Element	Max. Recommended Current [A]
10C Temperature Rise	4 Amps per conductor @ 25°C A

#### Voltage

UL Voltage Rating 300 V RMS

# **Temperature Range**

	UL Temp Rating:	75°C
1	Operating Temp Range:	-20°C To +75°C

# **Mechanical Characteristics**

Bulk Cable Weight:	30 lbs/1000ft
Max Recommended Pulling Tension:	103.6 lbs
Min Bend Radius/Minor Axis:	1.8 in

#### **Standards**

NEC Articles:	800
NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMG
CPR Euroclass:	Eca

# Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

# Suitability

	Suitability - Indoor:	Yes	
--	-----------------------	-----	--

# Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1666 Riser
CSA Flammability:	FT4
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

### Plenum/Non-Plenum

Plenum Number:	6302FE

# Part Number

### Variants

ltem #	Color	Footnote
5302FE.00152	Chrome	
5302FE.00305	Chrome	
5302FE.00U305	Chrome	
5302FE 0081000	Gray	С
5302FE 008500	Gray	
5302FE 008C250	Gray	
5302FE 008U1000	Gray	
5302FE 008U500	Gray	
Footnote:		

#### © 2019 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.