





UPC Code: 078477226506 Country Of Origin: Mexico



# **5225**

15 Amp, 120 Volt, Duplex Style Single-Pole / 5-15R AC Combination Switch, Commercial Grade, Grounding, Side Wired, - Brown

With Leviton's extensive assortment of combination devices, you can fill a one-gang space with two switches, a switch and receptacle, even a switch and GFCI. From sensor guide lights to multi-purpose styles and Tamper-Resistant receptacles, we accommodate your every need. These devices come in a range of colors and are backed by a limited two-year warranty. Built to last and designed to save space, these attractively styled devices are at home in any setting.

#### **Technical Information**

AC Horsepower Ratings
HP Rating: 1/2HP-120V
Max. Amperage: 12 Amp
Electrical Specifications

Dielectric Voltage: Withstands 1500V

for 1 minute

**Grounding:** Grounding

Overload UL20 Test: 100 cycles of OL

at 4.8 times rated current
Receptacle Amperage: 15 Amp
Receptacle Voltage: 125V AC
Switch Amperage: 15 Amp
Switch Voltage: 120V AC

Temperature Rise: Maximum 30

degrees C rise

Environmental Specifications
Flammability: Rated V-2 per UL 94

Operating Temperature: -40°C to 65°C

Material Specifications

Actuator Material: Thermoplastic Body Material: Thermoplastic

Color: Brown

Strap Material: Steel

Mechanical Specifications

Product ID: Stamped on Strap

Terminal Accom.: 14-12 AWG

Terminal ID: Brass-Hot Black-Hot

White-Neutral Green-Gnd

Termination: Side

Torque Range: 12-14 inch pounds

Product Features
Amperage: 15 A
Color: Brown
NEMA: 5-15R

Type: Duplex Style Combination Switch

Voltage: 120 VAC Warranty: 2 Year Limited

Standards and Certifications

**ANSI:** C-73

CSA C22.2 No. 111: File #152105

NEMA: WD-1 & WD-6


**NOM:** 057

UL Standard: UL 20 Warranty: 2 Year Limited

#### **Features and Benefits**

- AC quiet switches have silver-cadmium oxide contacts and receptacles have double-wipe contacts for maximum conductivity
- All devices have grounding screw
- Side wired with terminal screws that accept up to #12 copper or copper-clad wire
- Fit standard wallboxes
- Break-off tabs on devices with AC quiet switches permit conversion to seperate feeds
- Backed by a Limited Two-Year Warranty

# **Dimensional Diagram**



### SPECIFICATION SUBMITTAL

١	JOB NAME:	CATALOG NUMBERS:	
I			
I	JOB NUMBER:		

### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

 $\label{eq:thm:condition} \textbf{Telephone: +1-800-323-8920} \cdot \textbf{FAX: +1-800-832-9538} \cdot \textbf{Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005}$ 

### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

## Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

