



UPC Code: 078477764961

Country Of Origin: China

NEMA:
5-15R



GFTR1-MW

15 Amp, 125 Volt Receptacle/Outlet, 20 Amp Feed-Through, Tamper-Resistant, Self-test SmartlockPro GFCI, Monochromatic, back and side wired, midway sized nylon wallplate/faceplate, screws and self-grounding clip included - White

Peace of mind, all the time. The SmartlockPro Self-Test GFCI tests itself even if you forget. Designed to meet the latest UL standard for auto-monitoring (self-test) our complete line of self-test GFCIs periodically conduct an automatic internal test to confirm that it can respond to a ground fault. With the slimmest profile on the market, the device allows for fast and easy installation, while Leviton's patented reset lockout mechanism prevents reset of the GFCI if it is not wired or operating correctly. The SmartlockPro Self-Test GFCI is the smart choice in ground fault circuit interrupter protection.

Technical Information

Product Features

Amperage: 15 A
At Rated Voltage: 1 HP
Brand: SmartlockPro
Color: White
Feature: Self-Test
Fed Spec WC-596: Yes
Grade: Residential/Commercial Specification Grade
Grounding: Self Grounding
NEMA: 5-15R
Pole: 2
Standards and Certifications: UL/CSA
Strap Material: Galvanized Steel
Tamper Resistant: Yes
Termination: Back & Side
Trip Level: Class A, 5mA plus or minus 1mA
Type: Standard Duplex
Voltage: 125 VAC
Warranty: 2-Year Limited
Wire: 3

AC Horsepower Ratings

At Rated Voltage: 1 HP
Dielectric Voltage: Withstands 1250VAC per UL 943 and CSA-C22.2 No. 144.1-06
Short Circuit Current Rating: 10KA
Temperature Rise: Max 30C after 100 cycles OL at 150 percent rated current

Electrical Specifications

Dielectric Voltage: Withstands 1250VAC per UL 943 and CSA-C22.2 No. 144.1-06
Flammability: Rated V-2 per UL 94
Operating Temperature: -35C to +66C
Short Circuit Current Rating: 10KA
Temperature Rise: Max 30C after 100 cycles OL at 150 percent rated current

Environmental Specifications

Clamps: Brass
Face Material: Thermoplastic
Grounding Screw: Plated Steel
Line Contacts: Brass Double Wipe .031 Thick
Notes: w/ Midway Sized Wallplate
Product ID: Ratings are permanently marked on device
Terminal Accom.: 14-10 AWG
Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral
Terminal Screws: Plated Steel
Yoke: Zinc-Plated Steel

Mechanical Specifications

Amperage: 15 A
Brand: SmartlockPro
Color: White
Feature: Self-Test
Fed Spec WC-596: Yes
Grade: Residential/Commercial Specification Grade
Grounding: Self Grounding
NEMA: 5-15R
Pole: 2
Product ID: Ratings are permanently marked on device
Standards and Certifications: UL/CSA
Strap Material: Galvanized Steel
Tamper Resistant: Yes
Terminal Accom.: 14-10 AWG
Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral
Termination: Back & Side
Trip Level: Class A, 5mA plus or minus 1mA
Type: Standard Duplex
Voltage: 125 VAC
Warranty: 2-Year Limited
Wire: 3

Standards and Certifications

Body Material: Polycarbonate
Clamps: Brass
Face Material: Thermoplastic
Grounding Screw: Plated Steel
Line Contacts: Brass Double Wipe .031 Thick
Notes: w/ Midway Sized Wallplate
Operating Temperature: -35C to +66C
Terminal Screws: Plated Steel
Yoke: Zinc-Plated Steel

ANSI: C-73
CSA C22.2 No. 42: Yes
CSA-C22.2 No. 144.1-06: File LR-57811
MIL-SPEC: A-A-55459-SB
NOM: Yes
UL 943: File E48380
UL498: Yes

Material Specifications

Body Material: Polycarbonate

Features and Benefits

- Provides continuous ground fault protection – detects and trips on actual ground fault even when self-test is being conducted
- On initial power up, tests the GFCI within 3 seconds
- Auto-monitoring exceeds the UL requirement
- Auto adapts and shifts to more frequent testing if potential problem is detected
- Status Indicator Light provides simple, intuitive feedback on power and protection status as well as indication of line/load reversal
- Patented Lockout Action prevents reset if GFCI is damaged and cannot respond to a ground fault
- Electronics are designed to minimize any false triggers
- Reduced depth makes it easier to install in any electrical box, even shallow ones
- Terminals allow for easy wiring options – back and side wire capable
- External back wire clamps provide visual indication of proper wire seating
- Withstands high torque and resists wire pullout
- Standard brass self-grounding clip
- Trip threshold meets or exceeds UL requirements for tripping time
- Improved immunity to high-frequency noise reduces nuisance tripping
- Advanced electronics design provides superior resistance to electrical surges and over-voltages
- Compatible with all Decora devices and wallplates; available in select Decora colors
- UL Fed Spec WC-596 rated.

SPECIFICATION SUBMITTAL

JOB NAME: <input style="width: 95%; height: 20px;" type="text"/>	CATALOG NUMBERS: <input style="width: 65%; height: 20px;" type="text"/> <input style="width: 30%; height: 20px;" type="text"/>	
JOB NUMBER: <input style="width: 95%; height: 20px;" type="text"/>	<input style="width: 65%; height: 20px;" type="text"/> <input style="width: 30%; height: 20px;" type="text"/>	

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):
+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-
1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

