

[Custom Capabilities](#)[Test Accessories](#)[Plugs, Jacks, Posts](#)[Connectors](#)[Hardware](#)[Spacers](#)[Home](#)[About Abbatron](#)[Products](#)[Locate Distributor
or Representative](#)[Contact Us](#)[Request Information](#)[Site Map](#)

Ceramic Spacers

- Ceramic spacers are Grade L-5 Steatite, glazed and fired at high temperature
- Threaded from each end as indicated in table
- Continuous safe operating Temperature Rating of 930°C(1700°F)
- Other size Options are available from factory in quantity, as are spacers with sizes at each end for adaption applications

 Ceramic Spacers drawing[Inventory Search](#)[Cross Reference](#)[UPS Tracking](#)

632 Arch Street, POB 726
Meadville, PA 16335 USA
814-724-6440
Contact Webmaster
© 2006

PART NO.	LENGTH	O.D.	THREAD		MIL NUMBER
			SIZE	DEPTH	
2640	1/4	1/4	6-32	THRU	
2642	3/8	3/8		5/32	
2641	1/2	1/4		3/16	
2643		3/8		5/32	
2600		1/2		9/64	NL 523 VW01 004
2644		3/8		1/4	NL 523 VW01 005
2601	5/8	1/2	8-32	3/16	NL 523 VW02 005
2602	3/4	3/8	6-32	1/4	NL 523 VW01 006
2645		1/2	8-32		NL 523 VW02 006
2608		3/8	6-32		NL 523 VW01 008
2603	1	1/2	8-32	3/8	NL 523 VW02 008
2646		3/4	10-32		NL 523 VW03 008
2609		3/8	6-32		NL 523 VW01 010
2615	1-1/4	1/2	8-32		NL 523 VW02 010
2604		3/4	10-32		NL 523 VW03 010
2610		1	1/4-20	7/16	NL 523 VW04 010
2616	1-1/2	1/2	6-32	3/8	NL 523 VW01 012
2622		3/8	8-32		NL 523 VW02 012
2647		1/2	10-32		NL 523 VW03 012
2605		1	1/4-20		NL 523 VW04 012
2611	2	3/8	6-32	3/8	NL 523 VW01 016
2612		1/2	8-32		NL 523 VW02 016
2618		3/4	10-32		NL 523 VW03 016
2624		1	1/4-20		NL 523 VW04 016
2648	2-1/2	1/2	6-32	3/8	NL 523 VW02 020
2613		3/8	8-32		NL 523 VW03 020
2619		1/2	10-32		NL 523 VW04 020
2649		3/4	1/4-20		NL 523 VW01 024
2625	3	1/2	6-32	3/8	NL 523 VW02 024
2614		3/8	8-32		NL 523 VW03 024
2620		1/2	10-32		NL 523 VW04 024
2626	4	1	1/4-20	3/8	NL 523 VW03 032
2650		3/4	10-32		NL 523 VW04 032
2621		1	1/4-20		NL 523 VW04 040
2627	5	1	1/4-20	5/8	NL 523 VW04 048
2628	6				

Maximum Thread Depth					
Thread Size	2 - 56	4 - 40	6 - 32	8 - 32	10 - 32
Thread Length	0.375	0.500	1.000	1.000	1.000
Tapped Thru					
Thread Length	0.250	0.375	0.375	0.375	0.375
Tap each end					

[home](#) | [about abbatron](#) | [products](#) | [locate distributor or representative](#) | [contact us](#) | [request information](#) | [site map](#)