



<b>EAN:</b>	4013288031761	<b>Size:</b>	45x6x6 mm
<b>Part number:</b>	05064150001	<b>Weight:</b>	7 g
<b>Article number:</b>	867/12 TORX®	<b>Country of origin:</b>	CZ
		<b>Customs tariff number:</b>	82079030

- For recessed TORX® screws
- Ductile and tough for hard materials
- Thread drive M 5 (Wera connecting series 12)
- Suitable for Böllhoff/Uniquick, Holz-Her, Weber
- Prevents premature breakage of the drive tip

High quality bits for recessed TORX® screws. Tough viscous for universal use. Thread drive M 5.

**Web link**

[http://products.wera.de/en/bits\\_holders\\_adaptors\\_the\\_range\\_of\\_bits\\_bits\\_for\\_torx\\_screws\\_867\\_12\\_\\_torx.html](http://products.wera.de/en/bits_holders_adaptors_the_range_of_bits_bits_for_torx_screws_867_12__torx.html)

Wera - 867/12 TORX®  
05064150001 - 4013288031761

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

Bits for TORX® Screws

Thread drive M 5 (Wera connecting series 12)







Thread drive M 5 (Wera connecting series 12). Drive: For direct machine drive. Suitable for: Böllhoff/Uniquick, Holz-Her, Weber.

Tough-absorbing bits



Tough-absorbing Wera bits (Z) prevent any premature breakage of the drive tip.

Further versions in this product family:

				
		mm	inch	mm
05064148001	TX 10	45	1 3/4	6.0
<b>05064150001</b>	<b>TX 15</b>	<b>45</b>	<b>1 3/4</b>	<b>6.0</b>
05064155001	TX 20	45	1 3/4	6.0
05064160001	TX 25	45	1 3/4	6.0

Web link

[http://products.wera.de/en/bits\\_holders\\_adaptors\\_the\\_range\\_of\\_bits\\_bits\\_for\\_torx\\_screws\\_867\\_12\\_\\_torx.html](http://products.wera.de/en/bits_holders_adaptors_the_range_of_bits_bits_for_torx_screws_867_12__torx.html)

Wera - 867/12 TORX®  
05064150001 - 4013288031761

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: info@wera.de