



EAN:	4013288201003	Size:	40x4x4 mm
Part number:	05300025001	Weight:	2 g
Article number:	867/21 IPR TORX® PLUS	Country of origin:	CZ
		Customs tariff number:	82079030

- For recessed five lobe screws with safety pin
- Five lobe profile with bore hole on the output side
- Ductile and tough for hard materials
- 4 mm halfmoon drive (Wera connecting series 9)
- Suitable for Delvo, Densei, etc.

A 5-flank TORX PLUS® profile with bore hole. Tough viscous for universal use. Drive: HIOS 4 mm.

Web link

http://products.wera.de/en/bits_holders_adaptors_the_range_of_bits_bits_for_tamper-proof_torx_plus_ipr_screws_with_safety_pin_867_21_ipr_torx_plus.html

Wera - 867/21 IPR TORX® PLUS
05300025001 - 4013288201003

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Bits for Tamper-proof TORX PLUS® IPR Screws with Safety Pin

For recessed TORX PLUS® IPR screws with safety pin

4 mm HIOS direct drive

Tough-absorbing bits



A 5-flank TORX PLUS® profile with a borehole. This drive geometry has only five flanks instead of the usual six and a borehole to protect safety screws against unauthorised unfastening. The screws cannot be turned with conventional, widely available tools.



HIOS, 4mm, Wera Series 21. Drive: For direct machine drive. Suitable for: BL-5000, CL-2000, CL-3000, CL-4000, SS-3000, SS-4000, L-4500, L-5000, CD-4000, CD-5000, VZ-1510 (incl. PS-type).



Tough-absorbing Wera bits (Z) prevent any premature breakage of the drive tip.

Further versions in this product family:



mm



inch



mm

		mm	inch	mm
05300025001	1 IPR	40	1 37/64	1.8
05300037001	1 IPR	60	2 3/8	1.8

Web link

http://products.wera.de/en/bits_holders_adaptors_the_range_of_bits_bits_for_tamper-proof_torx_plus_ipr_screws_with_safety_pin_867_21_ipr_torx_plus.html

Wera - 867/21 IPR TORX® PLUS
05300025001 - 4013288201003

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de