

N-67A

Electrical Specifications (@25°C)

1. Maximum Power: 150 VA
2. Input Voltage:
 - Parallel: 115V@50/60Hz
 - Series: 230V@50/60Hz
3. Output Voltage: 115V ± 5%
4. Full Secondary Load: 1.3 Amps RMS
5. Voltage Regulation: 5 % TYP @ full load to no load

Description:

The N-67A is a power transformer for isolating equipment from direct connection to the powerline. The primary and secondary coils are concentrically wound providing excellent magnetic coupling. Having good magnetic coupling between windings helps reduce leakage flux and phase shift.

Safety:

These units are designed with 2100V isolation between winding to winding and between winding and core. Materials and construction are rated for Class B insulation system.

Dimensions: Unit: In inches


A	B	C	D	E	F
3.875	3.281	3.875	2.50	3.00	2.00

Weight: 7.0 Lbs.

Mounting Holes: .375 x .187"

Connections: 10.0±1" leads, 0.250±0.062" Skin & Tin

Schematic:



INPUT - Series: BLK to BLK/GRN, JUMPER BLK/YEL to BLK/RED

Parallel: BLK to BLK/YEL, JUMPER BLK to BLK/RED and BLK/YEL to BLK/GRN

OUTPUT: RED to RED

SHIELD: WHT

RoHS Compliance: As of manufacturing date February 2005, all standard products meet the requirements of 2011/65/EU, known as the RoHS initiative.

* Upon printing, this document is considered "uncontrolled". Please contact Triad Magnetics' website for the most current version.

