

## Datasheet

### Crimp Tool for Ferrules

RS Stock number: 683-1605



#### Specifications:

- Non slip main handle and low friction moving handle ensure a comfortable hand grip
- Provides two-hand grip in the final phase of crimping, increasing comfort and productivity
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear mis-crimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- Each tool has a unique serial number for traceability
- Durable: life span exceeds 50,000 cycles
- High strength, through hardened alloy Swedish steel construction

Crimp nest: 0.25-0.75 mm<sup>2</sup> / AWG 24-20

1.0-1.5 mm<sup>2</sup> / AWG 18-16

2.5 mm<sup>2</sup> / AWG 14

4.0 mm<sup>2</sup> / AWG 12

6.0 mm<sup>2</sup> / AWG 10

Wire size: 0.25-6 mm<sup>2</sup> / AWG 24-10

Connector: Uninsulated and Insulated Ferrules

Description: For ferrules, both uninsulated and insulated

Crimp profile: Trapez-Crimp

Length: 198 mm / 7.8"

Width: 18 mm / 0.71"

Height: 59 mm / 2.32"

Weight: 558 g / 0.79 lb

Life span, cycles: 50,000