

## Crimping pliers - CRIMPFOX-SC 1,5 - 1212048

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Crimping pliers, for non-insulated slip-on sleeves 2.8 and 4.8 mm, 0.1 - 1.5 mm<sup>2</sup>, B crimp

### Your advantages

- Consistently high crimping quality
- Marked die stations for precise processing of corresponding cross sections
- Unlockable pressure lock



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 453837
GTIN	4046356453837

### Technical data

#### Dimensions

Length (b)	198 mm
Width (a)	18 mm
Height (c)	59 mm

#### General

Color	black
Compression	B crimp
Type of contact	Slip-on sleeve
Designation	Crimping position 1
Min. cross section	0.1 mm <sup>2</sup>
Max. cross section	0.5 mm <sup>2</sup>
AWG min	26
AWG max	22

# Crimping pliers - CRIMPFOX-SC 1,5 - 1212048

## Technical data

### General


Designation	Crimping position 2
Min. cross section	0.5 mm <sup>2</sup>
Max. cross section	1 mm <sup>2</sup>
AWG min	22
AWG max	18
Designation	Crimping position 3
Min. cross section	0.5 mm <sup>2</sup>
Max. cross section	1.5 mm <sup>2</sup>
AWG min	18
AWG max	16
Die station	Crimping position 4
	Crimping position 5
Weight	350 g
Min. cross section	0.1 mm <sup>2</sup>
Max. cross section	1.5 mm <sup>2</sup>
AWG min	26
AWG max	16

### Environmental Product Compliance

California Proposition 65	Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration
---------------------------	---

## Drawings

Product drawing



## Approvals

Approvals

---

Approvals

EAC

---

## Crimping pliers - CRIMPFOX-SC 1,5 - 1212048

### Approvals

Ex Approvals

---

#### Approval details

EAC



RU x-  
DE.xx08.B.02974

---

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>