



Datasheet Programmable Switching D.C. Power Supply





The IPS-Series is single output, 200W, programmable switching DC power supplies. OVL, OCL, OTP, and OPL protect the IPS-Series and its loads from unexpected conditions. The IPS-Series has a large LCD panel with output and parameter views and a key lock feature to prevent changing the settings. The IPS-Series is suitable for generic bench-top applications in laboratories and educational institutions.

FEATURES

- LCD Display
- Output ON/OFF Control
- 3 Step Fan Speed Control
- Voltage/Current/Power Setting
- Key Lock to Avoid Error Operation
- Normal, +% & -% Output Operation Key
- Standard Interface: RS-232C

Rear Panel







| SPECIFICATIONS | | | |
|--|------------------------------|------------------------------------|------------------------------------|
| OUTPUT Model | IPS-603 | IPS-405 | IPS-2010 |
| | | | |
| Voltage | 0 ~ 60V | 0 ~ 40V | 0 ~ 20V |
| Current | 0 ~ 3.5A | 0~5A | 0 ~ 10A |
| VOLTAGE REGULATION | | | |
| Load | ≤ 10mV ≤ 0.05% | ≤ 10mV ≤ 0.05% | ≤ 10mV ≤ 0.05% |
| Line | ≤ 0.05% | ≤ 0.05% | ≤ 0.05% |
| CURRENT REGULATION | | | |
| Load | ≤ 5mA | ≤ 5mA | ≤ 5mA |
| Line | ≤ 0.05% | ≤ 0.05% | ≤ 0.05% |
| RIPPLE | | | |
| Voltage (mVrms) | < 20mV | < 20mV | < 20mV |
| Current (mArms) | ≤ 20mV ≤ 10mA | ≤ 20mV ≤ 10mA | ≤ 20mV ≤ 10mA |
| RESOLUTION | | | |
| Voltage | 20mV | 10mV | 10mV |
| Current | 20mV | 2mA | 5mA |
| PROGRAM ACCURACY | 21177 | 21101 | 31117 |
| Voltage | \pm 0.05%rdg \pm 4digits | <u>+</u> 0.05%rdg <u>+</u> 3digits | <u>+</u> 0.05%rdg <u>+</u> 3digits |
| Current | ± 0.1%rdg + 5digits | ± 0.1%rdg + 5digits | ± 0.3%rdg + 10digits |
| READBACK (METER) RESOLUTI | | _ 0.170106 1 3016103 | _ 0.370146 + 1041615 |
| Voltage | Same as Resolution | Same as Resolution | Same as Resolution |
| Current | Same as Resolution | Same as Resolution | Same as Resolution |
| READBACK (METER) ACCURACY | | | |
| Voltage | Same as Program Accuracy | Same as Program Accuracy | Same as Program Accuracy |
| Current | Same as Program Accuracy | Same as Program Accuracy | Same as Program Accuracy |
| PROTECTION | | | |
| OVL/OCL/OPL/OTP | <u> </u> | V | V |
| OUTPUT ON/OFF CONTROL | V | V | V |
| DISPLAY | V | V | V |
| LCD | | | |
| INTERFACE (STANDARD) | | | |
| RS-232C | | | |
| POWER SOURCE | | | |
| AC 115V±10%, AC 230V±15%, 50/60Hz | | | |
| DIMENSIONS & WEIGHT | | | |
| 225(W) x 100(H) x 305(D) mm ; Approx. 4kg | | | |
| Specifications subject to change without notice. | | | |

Specifications subject to change without notice.

ORDERING INFORMATION

IPS-603200W Programmable Switching DC Power SupplyIPS-405200W Programmable Switching DC Power SupplyIPS-2010200W Programmable Switching DC Power Supply

ACCESSORIES

User manual x 1, Power cord x 1, Test lead GTL-104A x 1,

OPTIONAL ASSESSORIES

GTL-232A RS-232C Cable

FREE DOWNLOAD

PC Software RS-232C Remote Control Software

