



ENGLISH

12W Plug And Go Range



Features:

- Universal Full Range AC Input
- Interchangeable AC Heads
- Level 6 Efficiency
- Cost Effective & Highly Reliable
- 1 Year Warranty



ENGLISH

Characteristics

Part Number	T6328ST	T6329ST	T6330ST	T6331ST	T6332ST	T6333ST
RS Stock Number	1244702	1244703	1244704	1244705	1244706	1244707
Output Voltage	5Vdc	6Vdc	9Vdc	12Vdc	15Vdc	24Vdc
Output Current Max	2.4A	2A	1.33A	1A	1A	500mA
Power Watts	12w	12w	12w	12w	15w	12w
Line Regulation	+/-2% Max					
Hold Up Time	10mS min.					
Ripple & Noise (mV p-p)	200mV p-p					
Protections	Input Protection Output Protection Short Circuit Protection					
Rated Input Voltage	100-240Vac					
Full Input Voltage Range	90-264Vac					
Rated Frequency	47-63Hz					
Efficiency	≥ 82.95% @ average of 25/50/75/100% loads 115V&230VAC input					
Inrush Current	50A Max					
Input Power (No Load)	0.1A Max					
AC Inlet	UK,Euro,US,Aus Interchangeable Plugtops					
DC Cord	1.5m Output Cable					
DC Plug	2.1mm C+ve					
Hi-Pot Specification	Primary to Secondary :AC 3000Vrms, 4 mA , 1 minute for type test					
Insulation Resistance	Primary to secondary: 50M OHM to 500VDC					
Operating Temperature	0°C ~ +40°C					
Storage Temperature	-20°C ~ +70 °C					
Storage Humidity	10% ~ 95%					
Safety Approvals	CE, C-Tick, UL, TUV, GS					
Dimensions (mm)	71.38cm(L) x 40.95cm(W) x 34.31cm(H)					