

# 311 Series - Industrial Sequencing DPDT, 5 Amp



File No. ES2197



The 311 Series relays are sequencing (stepper) relays built on the industrial 219 style frame. Hold down clip is integral to the relay base. Double pole contacts transfer on energizing of coil or de-energizing. Dual cam movement allows contacts to operate together or separately. Works equally well with application of continuous voltage to coil or energy saving impulse. No continuous voltage required for memory. Numerous custom switching arrangements are possible over 8 steps per revolution of the cams.

## GENERAL SPECIFICATIONS (@ 25° C)

### Contacts:

Contact Configuration	DPDT
Contact Material	Silver Alloy
Contact Rating	
125 / 250VAC Resistive	5 Amp
28VDC Resistive	5 Amp
Contact Resistance, Initial	100 milliohms max @ 6VDC

### Coil:

Coils Available	AC or DC up to 300V
Nominal Coil Power	4.9VA 1.8W
Input Voltage Tolerance - AC	85% to 110% of nominal
Input Voltage Tolerance - DC	80% to 110% of nominal
Drop out voltage	10% of nominal
Duty	Continuous

### Timing:

Operate Time (max)	35mS
Release Time (max)	35mS

### Dielectric Strength:

Across Open Contacts	1500Vrms
Between Mutally Insulated Points	1500Vrms
Insulation Resistance	1,000 Megohms min @ 500VDC

### Temperature:

Operating	-20 to 60°C (-4 to 140°F)
Storage	-40 to 105°C (-40 to 221°F)

### Life Expectancy:


Electrical (full load operations)	100,000
Mechanical (no load operations)	5,000,000

### Miscellaneous:

Mounting Position	Any
Mating Socket	27390D
Enclosure	Clear Polycarbonate
Weight	7.5oz (190 grams)



311 Wire Diagram  
(Top View)




311XBP  
311XBPR\*  
\*Transfer on release

# Latching / Sequencing Relays

## 10 - 100 Amp

Max Outline Dimensions  
Dimensions Shown in inches & (millimeters)



Section 4

### Coil Specifications

AC Coil, 50/60HZ		DC Coil	
Nominal voltage	Resistance ohms ±10%	Nominal voltage	Resistance ohms ±10%
6	1.1	6	15.5
12	4.2	12	63.5
24	15.5	24	250
120	540	48	970
240	1815	110-125	6200

**Ordering Code** 311 XBX P R L -120VAC

**Series**  
311

**Contact Arrangement**  
XBX (DPDT) - (2 form C)

**Standard Features**  
Plug-in with polycarbonate cover - CODE P

**Contact Transfer**  
When coil is energized - NO CODE  
When coil is de-energized - CODE R

**Optional Features**  
Indicator lamp - CODE L  
Coil suppression - CODE V

**Coil Voltage**  
AC: 6, 12, 24, 120, 240 (Add VAC)  
DC: 6, 12, 24, 115-125 (Add VDC)