



FEATURES:

- ✓ Accepts standard banana plug, wire or spade lug.
- ✓ Mounts in panels from .070" to .250" (1.77mm to 6.35mm) thick.

MATERIALS:

- Insulated Captive Thumb Nut: Brass
- Insulation: Polycarbonate
- Mounting Base: Polycarbonate
- Insulator: Polycarbonate
- Lockwasher: Nickel Plated Steel
- Hex Nut: 1/4" #8-32 Nickel Plated Brass
- Binding Post:
- Finish: 3750 – Gold plated brass
- 3760 – Bright tin plated brass
- 3770 – Gold plated Tellurium Copper

RATINGS:

- Operating Voltage: Hands free usage in controlled voltage environments: 2500 Vrms maximum. *For CE compliance: not intended for hand-held use at voltage above 33 Vrms/70 Vdc.*
- Operating Temperature: +239°F (+115°C) Max.
- Current: 15 Amperes

ORDERING INFORMATION:

- Model: 3750-**Color** (Gold plated brass) *Ordering Example: 3770-2 (Red, Gold Plated Tellurium Copper)*
- Model: 3760-**Color** (Bright tin plated brass)
- Model: 3770-**Color** (Gold Plated Tellurium Copper)

Color =: Color, 0 (Black), 1 (Brown), 2 (Red), 3 (Orange), 4 (Yellow), 5 (Green), 6 (Blue), 7 (Violet), 8 (Gray), 9 (White)

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).
 All specifications are to the latest revisions. Specifications are subject to change without notice.
 Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technicalsupport@pomonatest.com)
 For "Where to Buy" information, visit the Pomona web site at www.pomonaelectronics.com