



Mallory Sonalert Products, Inc.

Part #: **SCE016XD3MG1W**

Sales Outline Drawing

Revision: **C**

Specifications:

Sound Level Category:	Extra Loud	Extra Loud		
Mode of Operation:	Continuous	Slow Pulse		
Loudness @ 2 FT:	95 to 105 dB(A) Typ.	95 to 105 dB(A) Typ.		
Pulse Rate (PPS):	N/A	1		
Frequency:	2900 ± 500 Hz	2900 ± 500 Hz		
Connection:	Red Wire to (+); Black Wire to (-)	Red Wire(+); Black Wire(-); Yellow Wire(-)		
Voltage Rating:	6 to 16 VDC			
Current Draw:	40mA MAX			
Housing Material:	6/6 Nylon, Color: Black			
Storage Temperature:	-40° to +85° C			
Operating Temperature:	-40° to +85° C			
Panel Mounting:	Recommended hole size is 1.25"(31.75mm). Thread front will fit standard 30mm(1.181") hole.			
Knurled Nut:	Used to attach part to panel. The max recommended torque is 10 in-lbs.			
Weight (Typical):	1.6 oz (45g)			
NEMA 3R,4X, & 12:	Approved with use of ACC03.			
cUL Recognition:	cUL Recognized			
Options:	Please contact factory.			

Dimensions: Inches (mm)

cUL Recognized

ROHS Compliant

