

Professionally approved products.

Datasheet

7.5A Brown Automotive Blade Fuse, 32V

RS Stock number 563-576

Automotive Fuses:



Approvals:







AUE Midget Car Fuses

- 10.3øx38.1 mm (13/32x1-1/2 inch)
- Ampere Rating: 1,2,3,4,5,6,7-1/2, 10,15,20,25,30,35,40,50,60,70,80A
- Voltage Rating: 32V/125V/250V
- Caps: Gold Finish For High Performance
- Equivalent AGU and 5AG Fuses
- Option: Gold Plated Wire Element Available Inside With Indicator Light 30A and less



CBC European Car Bakelite Fuses

- 6ø x 25mm
- Voltage Rating: 32V and less

Ampere Rating	Body Color
5A	Yellow
8A	White
16A	Red
20A	Beige
25A	Blue
30A	Green

Equivalent GBC Fuses



AST (mini-blade type) Terminal Car Fuses

- Transparent Body
- Voltage Rating: 32V and less

Ampere Rating	Body Color
2A	Gray
3A	Violet
4A	Pink
5A	Tan
7-1/2A	Brown
10A	Red
15A	Lt. Blue
20A	Yellow
25A	Natural
30A	Lt. Green



Equivalent MIN and ATM Fuses



Professionally approved products.

Datasheet



ATQ (blade type) Terminal Car Fuses

- Transparent Body
- Voltage Rating: 32V and less

Ampere Rating	Body Color
2A	BlackishGreen
3A	Violet
4A	Pink
5A	Tan
7-1/2A	Brown
10A	Red
15A	Lt. Blue
20A	Yellow
25A	Natural
30A	Lt. Green
35A	Purple





- Equivalent ATO and ATC Fuses
- Option: Gold Plated Terminal Available




AMT (max-blade type) Terminal Car Fuses

- Transparent Body
- Voltage Rating: 32V and less

Ampere Rating	Body Color
20A	Yellow
30A	Lt. Green
35A	Lt. Red
40A	Orange
50A	Red
60A	Lt. Blue
70A	Tan
80A	Transparent

- Equivalent MAXI and MAX Fuses
- Option: Gold Plated Terminal Available



ANE Gold Plated High Performance Fuses

- Visible Through Mica Window
- Metal Element are 24 Kt, Gold Plated
- Voltage Rating: 32V
- Ampere Rating: 60,70,80,100, 130,150,175,200,225,250,275, 300,325,350,400,500
- Equivalent ANL Fuses
- Option: Other Colors for Housing Are Available
- High Performance Good For High Power Audio Systems Also Use For Lift trucks And Other Battery Operated Systems



Professionally approved products.

Datasheet



ALF Fuse Links – Protect Wiring Harness

- Female Type Connection
- Voltage Rating: 32V

Ampere Rating	Body Color
20A	White
30A	Pink
40A	Green
50A	Red
60A	Yellow
80A	Black
100A	Blue

- Equivalent FLF Fuses
- Visible Through Transparent Cover



ALM Fuse Links – Protect Wiring Harness

- Male Type Connection
- Voltage Rating: 32V

Ampere Rating	Body Color	
20A	White	
30A	Pink	
40A	Green	
50A	Red	
60A	Yellow	
80A	Black	
100A	Blue	

- Equivalent FLF Fuses
- Visible Through Transparent Cover