

Datasheet

ENGLISH

Lithium Polymer Portable Charger Power Bank

RS Stock number 775-7508



Based on Lithium Polymer battery technology, the PB-A5200 Power Bank can be used to charge a mobile phone battery or power portable equipment such as a Raspberry Pi computer board.

Specifications:

Capacity:

Charge Time:

Chemistry:

Depth:

Input Connector:

Input Voltage:

LED Indicator:

Length:

Maximum Output Current:

Number of Devices Supported:

Operating Temperature Range:

Output Connectors:

Output Voltage:

Series:

Weight:

Width:

5000 mAh

6 - 7 hours

Lithium Polymer

15.8 mm

Micro USB

5 V DC

Charge/Discharge, Power Levels

102 mm

2.1 A

2

0 - 35 °C

USB

5 V

Power Bank

154 g


66 mm

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.



Structural Drawing:





Safety Instructions:

Misuse, beat, crush, or drop and other conditions may cause product damaged.

Dropping and/or misuse of the product may cause malfunctions and/or damage.

Do not dispose of the power bank in heat and fire.

Please fully charge the power bank to activate it before first use.

If this product will not be used for a long time, please keep it in a cool and dry place. Charge and discharge one time per month.

If the power bank is not used, please turn off the power. Otherwise it will keep consuming the power.

At the end of the battery's life, it should be handed over to an appropriate collection point.

Accessories:

Micro USB charging cable

