



Identification	Part No.	Drawing	Dimensions in mm
<p>Hybrid cable, double ended, 4 x 2 x AWG 26/7 + 3 x 2.5 mm<sup>2</sup></p> <p>Length: a = 1 m      AC version                                  DC version</p> <p>          a = 5 m        AC version                                  DC version</p> <p>          a = 10 m     AC version                                  DC version</p> <p>          a = 20 m     AC version                                  DC version</p>	<p>33 57 211 0010 001 33 57 211 0010 002</p> <p>33 57 211 0050 001 33 57 211 0050 002</p> <p>33 57 211 0100 001 33 57 211 0100 002</p> <p>33 57 211 0200 001 33 57 211 0200 002</p>	<p>double ended</p> <p>Hybrid cable 8AWG 26/7+3x2.5</p> <p>Mating face RJ 45 according to IEC 60603-7</p> <p>a = length</p>	
<p>Hybrid cable, single ended, 4 x 2 x AWG 26/7 + 3 x 2.5 mm<sup>2</sup></p> <p>Length: a = 1 m      AC version                                  DC version</p> <p>          a = 5 m        AC version                                  DC version</p> <p>          a = 10 m     AC version                                  DC version</p> <p>          a = 20 m     AC version                                  DC version</p>	<p>33 57 111 0010 002 33 57 111 0010 001</p> <p>33 57 111 0050 002 33 57 111 0050 001</p> <p>33 57 111 0100 002 33 57 111 0100 001</p> <p>33 57 111 0200 002 33 57 111 0200 001</p>	<p>Protection level: IP 65 / IP 67</p> <p>Data part:            Transmission properties in accordance with                                  ISO/IEC 11801:2002: Class D</p> <p>single ended</p> <p>a = length</p>	
<p>Hybrid outdoor cable</p> <p>          Length: 10 m</p> <p>          Length: 20 m</p> <p>          Length: 500 m</p>	<p>33 57 851 0100 001</p> <p>33 57 851 0200 001</p> <p>33 57 851 5000 001</p>	<p>PVC jacket</p> <p>4 x 2 x AWG 26/7 + 3 x 2.5 mm<sup>2</sup></p> <p>Outer diameter: 12 mm</p> <p>Min. bending radius: single: 5 x OD repeated: 10 x OD</p>	

Further cable lengths are available on request